

Specification Sheet

Part Number: 596-00499

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC® & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Pre-printed labels offer significant time and cost savings over high-priced plastic engraved phenolic placards and the lead time of purchased markers.



Solar Label, Warning Turn off PV Prior to..., 4.125" x 2.0", VL, Orange/White, 50/roll

Article Number	596-00499
Type	WTOPVLBL
Color	Orange (OG)
Quantity Per	roll

Product Description	HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Short Description	Solar Label, Warning Turn off PV Prior to..., 4.125" x 2.0", VL, Orange/White, 50/roll
Global Part Name	WTOPVLBL-443/281-OG
Local Order Number 2	Cross Reference = 10 per pack: 596-00664; Metal Solar Placard 5 pack: 596-00832
Length L (Imperial)	4.125
Length L (Metric)	104.6
Width W (Imperial)	4.1
Width W (Metric)	104.14
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8

Width of Liner (Metric)	107.69
Width of Liner (Imperial)	4.24
Material	Type 443/281, UV-stabilised, flexible white vinyl with clear polyester laminate (443/281)
Material Shortcut	443/281
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	Yes
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2017 UL 969 NEC2014 NEC2020 NEC2023
Warranty (US)	Yes
UL Recognized (US)	Yes

Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1