




UDSK24-7/8"-19MM-F

Ruland UDSK24-7/8"-19MM-F, 7/8" x 19mm Double Universal Joint, Friction Bearing, Steel, Set Screw With Keyway, 1.495" (38.0mm) OD, 6.563" (166.7mm) Length





Description

Ruland UDSK24-7/8"-19MM-F is a double cardan friction bearing universal joint with 0.8750" x 19mm bores, 3/16" x 6mm keyways, 1.495" (38.0mm) OD, 6.563" (166.7mm) length, and 5/16-18 set screws. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UDSK24-7/8"-19MM-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT24/38-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

Keyway (K1) 3/16 in Keyway (K2) 6 mm B1 Max Shaft Penetration 1.400 in (35.6 mm) 1.400 in (35.6 mm) Joint Outer Diameter (OD) 1.495 in (38.0 mm) Bore Tolerance +0.0010 in / -0.0000 in (+0.025 / -0.000 mm) Length (L) 6.563 in (166.7 mm) Center Yoke Length (LC) 2.313 in (58.8 mm) Yoke Length (LY) 2.125 in (54.0 mm) Hub Depth (LH) 1.400 in (35.6 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Weight (Ibs) 2.318000 Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452937040 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application	Product Specifications			
B1 Max Shaft Penetration Joint Outer Diameter (OD) 1.495 in (38.0 mm) Bore Tolerance 1.400 in (35.6 mm) Length (L) 6.563 in (166.7 mm) Center Yoke Length (LC) 2.313 in (58.8 mm) Yoke Length (LY) 2.125 in (54.0 mm) Hub Depth (LH) 1.400 in (35.6 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm) Max Operating Angle 90° Material Specification Manufacturer Belden Universal Country of Origin USA Weight (Ibs) 2.318000 Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452937040 Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Bore (B1)	0.8750 in	Small Bore (B2)	19 mm
Joint Outer Diameter (OD) 1.495 in (38.0 mm) Bore Tolerance +0.0010 in /-0.0000 in (+0.025 /-0.000 mm) Length (L) 6.563 in (166.7 mm) Center Yoke Length (LC) 2.313 in (58.8 mm) Yoke Length (LY) 2.125 in (54.0 mm) Hub Depth (LH) 1.400 in (35.6 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Weight (Ibs) 2.318000 Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452937040 Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Keyway (K1)	3/16 in	Keyway (K2)	6 mm
/ -0.000 mm) Length (L) 6.563 in (166.7 mm) Center Yoke Length (LC) 2.313 in (58.8 mm) Yoke Length (LY) 2.125 in (54.0 mm) Hub Depth (LH) 1.400 in (35.6 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Weight (lbs) 2.318000 Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452937040 Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65	B1 Max Shaft Penetration	1.400 in (35.6 mm)	B2 Max Shaft Penetration	1.400 in (35.6 mm)
Yoke Length (LY) 2.125 in (54.0 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Weight (Ibs) 2.318000 Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452937040 Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Joint Outer Diameter (OD)	1.495 in (38.0 mm)	Bore Tolerance	+0.0010 in / -0.0000 in (+0.025 mm / -0.000 mm)
Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Weight (lbs) 2.318000 Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452937040 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Length (L)	6.563 in (166.7 mm)	Center Yoke Length (LC)	2.313 in (58.8 mm)
Peak Torque 9,000 in-lb (1,016.9 Nm) Rated Torque 1,800 in-lb (203.4 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Weight (lbs) 2.318000 Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452937040 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 ANARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Yoke Length (LY)	2.125 in (54.0 mm)	Hub Depth (LH)	1.400 in (35.6 mm)
Max Operating Angle90°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSAWeight (lbs)2.318000Recommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT24/38-NI-KITUPC63452937040Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicationProp 65▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Broached Set Screw	5/16-18	Screw Finish	Black Oxide
ManufacturerBelden UniversalCountry of OriginUSAWeight (lbs)2.318000Recommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT24/38-NI-KITUPC63452937040Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicationProp 65▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Peak Torque	9,000 in-lb (1,016.9 Nm)	Rated Torque	1,800 in-lb (203.4 Nm)
Weight (lbs) 2.318000 Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452937040 Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Max Operating Angle	90°	Material Specification	Alloy Steel
Matching Boot Cover UBOOT24/38-NI-KIT UPC 63452937040 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 ▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Manufacturer	Belden Universal	Country of Origin	USA
Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 △WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Weight (lbs)	2.318000	Recommended Lubricant	LUBRIPLATE No. 1200-2
Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 → WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Matching Boot Cover	UBOOT24/38-NI-KIT	UPC	63452937040
Prop 65 AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Tariff Code	8483.60.4000	UNSPC	25173810
California to cause cancer and birth defects or other reproductive harm. For more information go to	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	Prop 65	California to cause cancer and birth defects or other reproductive harm. For more information go to		