# TRIPP·LITE
## by EATON

# Smart 108 IP - 8-Port, Remote Access Cat5 KVM Switch for Rack Environments

## MODEL NUMBER: **0SU70032**



## Description

**Local or remote access to servers in the data center**

**Ideal for branch offices and growing companies**

**BIOS level, mixed platform access**

## Features

- 8 Ports
- Remote or Local Access
- BIOS level access
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cable
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

# Specifications

## Highlights

- 8 Ports
- Remote or Local Access
- BIOS level access
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cable
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

## System Requirements

Operating System

- Host & Remote: Windows, Linux

Resolution

- Target Server: 1600 X 1200 @ 85Hz
- Client Computer: Recommended that resolution should be higher than local computer resolution

## Package Includes

- Smart 108 IP Cat5 KVM Switch
- RS232 Download Cable
- Rackmount Kit
- Owner's Manual

| OVERVIEW | |
|---|---|
| UPC Code | 654518212143 |
| Console | Yes |

| PHYSICAL | |
|---|---|
| Color | Black |
| Shipping Weight (lbs.) | 7.70 |
| Shipping Weight (kg) | 3.49 |
| Unit Dimensions (hwd / in.) | 1.600 x 17.000 x 9.100 |
| Unit Dimensions (hwd / cm) | 4.1 X 43.1 X 23 |
| Unit Weight (lbs.) | 5.6 |
| Unit Weight (kg) | 2.54 |

| ENVIRONMENTAL | |
|---|---|
| Storage Temperature Range | -40 to 70 C / -40 to 158 F |
| Operating Temperature | 0 to 40 C / 32 to 104 F |

| COMMUNICATIONS | |
|---|---|
| Port Control | Hotkeys, OSD, Remote Toolbar |
| IP Remote Access | Yes |

| CONNECTIONS | |
|---|---|
| Number of Ports | 8 |
| PC/Server Connections | VGA; USB; PS/2 |

| FEATURES & SPECIFICATIONS | |
|---|---|
| NIAP-Certified Secure | No |
| Number of Users | 1 |

| WARRANTY & SUPPORT | |
|---|---|
| Product Warranty Period (Worldwide) | 3-year limited warranty |