




VMTSC100-40-M16-55-Z

Ruland VMTSC100-40-M16-55-Z, Vibration Isolation Mount, 100mm OD, M16 Threaded Stud, M16 Tapped Hole, 41mm Stud Length, 16mm Tapped Hole Depth, 40mm Height, 55 Shore A Natural Rubber Jacket, Steel




Description

Ruland VMTSC100-40-M16-55-Z is a vibration isolation mount with one tapped hole and one threaded stud. It has a 100mm outside diameter, M16 threaded stud, M16 tapped hole, 41mm stud length, 16mm tapped hole depth, and 40mm height. This vibration isolation mount is used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. It is often referred to as a sandwich mount or rubber buffer because it functions as shock or vibration isolator sandwiched between two machine components or surfaces. The threaded stud side of VMTSC100-40-M16-55-Z can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped hole on the component it will be mounted to. The tapped hole can be mounted to the system by threading it onto an existing stud on the component. VMTSC100-40-M16-55-Z has a rubber jacket that is made from natural rubber which has good elasticity. It has 55 Shore A hardness for a balance of rigidity and shock absorption. The zinc plated steel body allows for high strength and is suitable for most industrial applications. VMTSC100-40-M16-55-Z is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	3.94 in (100 mm)	Height (H1)	1.57 in (40 mm)
Thread (TH)	M16 x 2.0	Plate Thickness (PT)	0.12 in (3 mm)
Stud Length (LS)	1.61 in (41 mm)	Tapped Hole Depth (LT)	0.63 in (16.1 mm)
Spring Rate	11420.3 lb/in (2000 N/mm)	Shore Hardness	55A (+/- 5)
Max Deflection	0.39 in (9.9 mm)	Max Axial Load	4496.18 lb (20000 N)
Geometry	Cylindrical	Rubber Material	Natural Rubber
Metal Material	Zinc Plated Steel	Metallic Body Finish	Zinc-Plated
Manufacturer	JW Winco/ Otto Ganter	Country of Origin	Hungary
Weight (lbs)	1.631400	UPC	634529232507
Tariff Code	4016.99.6000	UNSPC	31162804

Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.

Prop 65  **WARNING** This product can expose you to the chemical Soots, known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.