# XVCTL1

Harmony XVC, Monolithic precabled tower light, plastic, red orange green, Ø40, base mounting, steady or flashing, buzzer, IP23, 24 V AC/DC



| Main                               |   |
|------------------------------------|---|
| Product or Component<br>Type       | Complete pre-wired monolithic tower light   |
| Beacon or indicator bank unit type | 3 illuminated units   |
| Sound signalling                   | Buzzer  |
| Mounting diameter                  | 1.57 in (40 mm)   |
| Device short name                  | XVC   |
| Light source                       | LED steady or flashing red<br>LED steady or flashing orange<br>LED steady or flashing green |
| Supply circuit type                | AC/DC   |

Complementary

| Complementary                          |   |  |
|--|---|--|
| Material                               | Polycarbonate illuminated unit                  |  |
|  | ABS (acrylonitrile butadiene-styrene) base unit |  |
|  | PBT + ABS (UL94-V0) top cover                   |  |
|  | SGP (chromium-plated) support tube              |  |
| Mounting Location                      | On support tube, 17 mm                          |  |
| [Us] rated supply voltage              | 24 V  |  |
| Cable cross section                    | 0.00 ln² (0.33 mm²)                             |  |
|  | 0.00 in <sup>2</sup> (0.83 mm <sup>2</sup> )    |  |
| AWG gauge                              | AWG 22  |  |
|  | AWG 18  |  |
| Cable length                           | 17.72 in (450 mm)                               |  |
| Marking                                | CE  |  |
| [Uimp] rated impulse withstand voltage | 4 kV  |  |
| Flashing frequency                     | 1 Hz  |  |
|  |   |  |

#### Environment

| Standards                             | EN/IEC 60947-1                                  |  |
|---------------------------------------|---|--|
|                                       | EN/IEC 60947-5-1                                |  |
| Product Certifications                | UL  |  |
| Protective treatment                  | TC  |  |
| Ambient Air Temperature for Storage   | -31158 °F (-3570 °C)                            |  |
| Ambient air temperature for operation | 14122 °F (-1050 °C)                             |  |
| Overvoltage category                  | Class I EN/IEC 61140                            |  |
| IP degree of protection               | IP23 vertical surface installation EN/IEC 60529 |  |

### Ordering and shipping details

| Category              | 22750 - INDUSTRIAL POINT OF PURCHASE |  |
|-----------------------|--------------------------------------|--|
| Discount Schedule     | IPOP                                 |  |
| GTIN                  | 785901557234                         |  |
| Nbr. of units in pkg. | 1                                    |  |
| Package weight(Lbs)   | 0.50 lb(US) (0.227 kg)               |  |
| Returnability         | Yes                                  |  |
| Country of origin     | MX                                   |  |

# Packing Units

| Unit Type of Package 1 | PCE                 |  |
|------------------------|---------------------|--|
| Package 1 Height       | 9.10 in (231.14 mm) |  |
| Package 1 width        | 2.30 in (58.42 mm)  |  |
| Package 1 Length       | 5.40 in (137.16 mm) |  |

### Offer Sustainability

| WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |  |
|---|--|
| Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration   |  |
| Yes   |  |
| ₫Yes  |  |
| China RoHS Declaration  |  |
| Product Environmental Profile   |  |
| ☐ End Of Life Information   |  |
| The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |  |
|   |  |