

Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 22.3 mm, Colour: Red

Business data

| | |
|--|---------------------------|
| Article number | <u>27144.9</u> |
| Article name | PQI 4/4 RD |
| GTIN (EAN) | 4044211225308 |
| Packaging unit | 20 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 4.53 g |
| Weight per piece (including packaging) | 4.68 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |
| Prio-Article | 27144.9 |
| Product description | Insulated cross-connector |

Technical data

Dimensions

| | |
|------------|---------|
| Length | 4 mm |
| Width | 22.3 mm |
| Height | 19.4 mm |
| Pitch size | 6.1 mm |

Ratings

| | |
|----------------------|-------------------|
| Max. voltage | 800 V |
| Rated current | 32 A |
| Current load, max. | 32 A |
| Rated cross-section | 4 mm ² |
| Contamination degree | 3 |

Connection data

| | |
|--------------|---|
| No. of poles | 4 |
|--------------|---|

Materials

| | |
|---------------------------|---------------|
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-0 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 120 °C |

Further technical data

| | |
|-------------------------------|---------|
| Mounting type | Plug in |
| Insulation available | ✓ |
| Touch protection is available | ✓ |
| Number of bridged terminals | 4 |

Environmental Product Compliance

| | |
|--------------------------------|-----|
| REACH Conform | yes |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Data sheet


27144.9 PQI 4/4 RD



Media

Accessories

##INVERSE##CONTA-CONNECT




Three-level initiator terminal | Multi-wire terminal, Push-in-connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5,1 mm, Colour: Grey

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------|---------------|----------------|
| <u>27040.2</u> | PIKD 2,5/SV/PE GNYE | 4044211227227 | 50 ST |



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Green-yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>27013.2</u> | PSL 4/2A GNYE | 4044211215804 | 50 ST |




Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Green-yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>27015.2</u> | PSL 4/3A GNYE | 4044211215842 | 50 ST |




Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Green-yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>27017.2</u> | PSL 4/4A GNYE | 4044211215880 | 50 ST |



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Grey


| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>27016.6</u> | PRK 4/4A GR | 4044211215873 | 50 |



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Grey

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>27012.6</u> | PRK 4/2A GR | 4044211215774 | 50 |

##INVERSE##CONTA-CONNECT



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Grey

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>27014.6</u> | PRK 4/3A GR | 4044211215835 | 50 |
