

Specification Sheet

Part Number: 166-90466

External NPT thread provides a secure connection.

Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.

Elbow features a smooth, swept bore to ease cable installation.

All-around "teeth" attach firmly to conduit and deliver a high extraction force.

Durable nylon material has high resistance to salts, oils, weak acids and solvents.

IP66 fitting has one-piece construction.



Article Number 166-90466

Type HG200-90-2000

Color Black (BK)

Quantity Per pack

Product Description HelaGuard Non-Metallic 90-Degree Elbow fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. IP66 ingress protection rated fittings.

| | |
|------------------------------|--|
| Short Description | HelaGuard Non-Metallic IP66 Fitting, 90-Elbow, 2" NPT Thread, 2" Dia, PA66, Black, 2/pkg |
| Global Part Name | HG200-90-2000-PA66-BK |
| Variant | 90° Elbow |
| Nominal Diameter (Imperial) | 2.63 |
| Nominal Diameter (Metric) | 67 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V-2 |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -58°F to +275°F (-50°C to +135°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| UL Recognized (US) | Yes |

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 2

Package Quantity (Metric) 2

Customs Number 3926909988