



NOTES

- 1 SMT LEAD-COPLANARITY: 0.1 MAX.
- 2 THIS PRODUCT HAS NO POLARITY TO MOUNT ON THE RECOMMENDED LAND PATTERN.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
△					△				

NO.	MATERIAL	FINISH, REMARKS	DESIGNED	CHECKED	APPROVED	RELEASED
3	PHOSPHOR BRONZE	TIN PLATED				
2	PHOSPHOR BRONZE	CONTACT AREA: GOLD (0.1μm) OVER NICKEL LEAD: GOLD PLATED (FLASH) OVER NICKEL				
1	LCP	BEIGE UL94V-0	J. Sakoda 99.10.18	M. Sakata 99.10.18	J. Yoshimura 99.10.18	

DRAWN	J. Sakoda 99.10.18	PART NO.	FX10B-14S-SV
NO.		DRAWING NO.	EDC3-151990
CODE NO. (OLD)	CL	SCALE	4 : 1
UNITS	mm		
HRS HIROSE ELECTRIC CO., LTD		CL570-0253-8	

TO
PCK