

Product data sheet

Characteristics

AK2GD12575

Cable duct - 75 x 125 mm - without cover - grey

Product availability: Stock - Normally stocked in distribution facility

Price*: 88.50 USD



Main

Product or Component Type	Cable duct
Accessory / separate part category	Cabling accessories
Range compatibility	Spacial (S3D) Spacial (CRN) Thalassa PLA Thalassa PLS Thalassa PLM
Device Composition	Without cover
Quantity per Set	Set of 8

Complementary

Color	Gray RAL 7030)
Fixing Mode	By screws Clip-on support
Material	PVC (polyvinyl chloride)
Height	2.95 In (75 mm)
Length	78.74 In (2000 mm)
Width	4.92 In (125 mm)
Net Weight	3.00 Lb(US) (1.36 kg)
Total number of wires	700

Environment

Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Flame retardance	V-0 UL 94
Fire resistance	1760 °F (960 °C) IEC 60695-2-1/1
Standards	VDE 0660 VDE 0506 DIN 43659

Ordering and shipping details

Category	22622-PANEL BUS_(OLD STYLE)
Discount Schedule	I
GTIN	3389110570496
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.91 In (15.0 cm)
Package 1 Width	10.24 In (26.0 cm)
Package 1 Length	78.74 In (200.0 cm)
Package 1 Weight	3.31 Lb(US) (1.5 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	72
Package 2 Height	30.31 In (77.0 cm)
Package 2 Width	110.24 In (280.0 cm)
Package 2 Length	47.24 In (120.0 cm)
Package 2 Weight	317.47 Lb(US) (144.0 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	8
Package 3 Height	5.91 In (15.0 cm)
Package 3 Width	10.24 In (26.0 cm)
Package 3 Length	78.74 In (200.0 cm)
Package 3 Weight	26.46 Lb(US) (12.0 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**