



## Connectors System AC 164 Panel Mounting

### AC 164 EBU/ 5 WS

socket, 5 pole, white, coding: 1 (mains), voltage rating: 240/400 V, current rating: 16 A, cross-section rating: 2.5 mm<sup>2</sup>, wall thickness min.: 0.5 mm, wall thickness max.: 1.2 mm



#### Order Info

reference number (ref.no.)	148655
PU	100
EAN	4028012123933

#### Type

type	socket
number of poles	5 pole
clamping units per pole	1
colour	white
coding	1 (mains)
cross-section rating	2.5 mm <sup>2</sup>
connection type	screw
PE function	yes
protection against incorrect plugging	yes
latch	yes

#### Technical Data

voltage rating	240/400 V
current rating	16 A
impulse voltage rating	4.0 kV
insulating material	PA
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	2.5 mm <sup>2</sup>
flammability rating	V-2
max. ambient temperature operation	70 °C
IP code	IP20
IP code when plugged	IP40
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes

<b>stripping length</b>	7.0 mm
<b>assembly contact screw</b>	PZ 1 / $\cup$ 0,5 Nm
<b>wall thickness min.</b>	0.5 mm
<b>wall thickness max.</b>	1.2 mm

## Approvals

<b>acc. to EN 61535</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>

## Accessories

<b>AC 164 VT 3/5 WS</b>	149755
-------------------------	--------