

Product data sheet

Specifications



Climasys Ultra thin resistance heater low starting current 20W 240V 130x250mm

NSYCRS25W240V

Main

Range	ClimaSys
Product name	ClimaSys CR
Product or component type	Ultra thin resistance heater
Power range	25 W
Input voltage	240 V AC 50/60 Hz
Electrical connection	Cable length: 2 m

Complementary

Operating position	Vertical Horizontal
Ambient air temperature for operation	-60...70 °C
Temperature setting range	-40...70 °C
Material	Silicone rubber
Height	110 mm external:
Width	230 mm external:
Depth	1.6 mm external:
Device composition	6 self-adhesive Velcro pads 6 plastic spacers 4 Telequick nuts 4 clip-on nuts fixing accessories
Condition of use	Heaters must be installed with a thermal controller Air sealed enclosure Electrical protection is needed
Fixing mode	By 4 screws
Mounting support	Standard mounting plate DIN rail Adhesive Velcro Telequick mounting plate

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm

Package 1 Width	25.5 cm
Package 1 Length	28 cm
Package 1 Weight	302 g
Unit Type of Package 2	CAR
Number of Units in Package 2	22
Package 2 Height	32 cm
Package 2 Width	51 cm
Package 2 Length	65 cm
Package 2 Weight	8.19 kg
Unit Type of Package 3	PAM
Number of Units in Package 3	330
Package 3 Height	171 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	135 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)