

1U Rack-Mount Console with 17-in. LCD, w/ KVM Cable Kit

MODEL NUMBER: **B021-000-17**



Description

Tripp Lite's B021-000-17 1U Rackmount Console features an integrated 17" LCD panel, full 88-key keyboard, and touch pad, all in a 1U rackmountable housing. The included KVM cable kit allows for connection to a PS/2 computer or KVM, and a PS/2 to USB adapter is included, which can be used to connect to a USB computer or KVM. The unit features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.. Your peripheral device connects to the USB type A port on the front of the unit, and your computer connects to the USB type A port on the back of the unit using a Tripp Lite UR020-Series type A M/M cable. Constructed of heavy-duty steel housing. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Space savings with 1U 19-inch, rack-mount drawer design
- Features 17-inch LCD TFT active-matrix, color panel
- Features a USB pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Supports resolutions of up to 1366 x 768
- Included PS/2 to USB adapter allows for connection to a USB computer or KVM
- Sleep mode when the monitor cover is closed
- Input 120/240 VAC
- Constructed of heavy-duty steel housing
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Highlights

- Control an entire network in just 1U of rack space; includes keyboard, 17" LCD screen, and touch pad
- Features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Connects to a PS/2 or USB server or KVM switch
- Supports video resolutions up to 1366 x 768
- Rackmountable in 19-inch system rack (1U), from 27" to 42" deep
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

- Computer or KVM with a VGA monitor port and USB or PS/2 keyboard/mouse ports

Package Includes

- 1- B021-000-17 1U Rackmount Console
- 1- KVM Cable Kit (HD15M to HD15M + 2 PS/2 Male)
- 1-PS/2 to USB Adapter
- 1- C13 to 5-15P Power Cord
- 1- User Manual

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332125279 |

| | |
|----------------------------------------------|-----------------------------------------------------|
| Technology | PS/2; VGA/SVGA |
| VIDEO | |
| Max Supported Video Resolution | 1366 x 768 @ 60Hz |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 127; 200; 208; 220; 230; 240 |
| Input Frequency | 50/60Hz |
| Input Current | 120V (1.2A) / 230V (0.7A) |
| Power Input Receptacle | IEC-320-C14 |
| POWER | |
| Power Consumption (Watts) | 30 |
| Power Consumption Detail | (Line Mode) 30W / (Standby Mode) 5W |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Green (CAPS LOCK, SCROLL LOCK, NUM LOCK) |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Steel (Steel, Electrogalvanized, Cold Rolled, Coil) |
| Rackmountable | Yes |
| Shipping Dimensions (hwd / in.) | 6.20 x 23.50 x 32.40 |
| Shipping Dimensions (hwd / cm) | 15.75 x 59.69 x 82.30 |
| Shipping Weight (lbs.) | 39.60 |
| Shipping Weight (kg) | 17.96 |
| Unit Dimensions (hwd / in.) | 1.710 x 17.690 x 28.440 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 28 |
| Unit Weight (kg) | 12.70 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 104 F (0 to 40 C) |
| Storage Temperature Range | -4 to 140 F (-20 to 60 C) |
| Relative Humidity | 20% to 90% RH, Non-Condensing |
| BTUs | (Line Mode) 102 BTU/Hr / (Standby Mode) 17.1 BTU/Hr |
| COMMUNICATIONS | |

| | |
|---------------------------------------|---------------------------------------------------------------------------------|
| IP Remote Access | No |
| CONNECTIONS | |
| Number of Ports | 1 |
| PC/Server Connections | VGA; USB; PS/2 |
| Side A - Connector 1 | HD15 (FEMALE) |
| Side A - Connector 2 | USB A (FEMALE) |
| Side B - Connector 1 | USB A (FEMALE) |
| Computer Keyboard and Mouse Interface | PS/2; USB |
| Computer Monitor Interface | VGA |
| FEATURES & SPECIFICATIONS | |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| NIAP-Certified Secure | No |
| Number of Users | 1 |
| Driver Required | No |
| BUILT-IN CONSOLE | |
| Console Screen Size (inches) | 17 |
| Console Screen Aspect Ratio | 16:9 |
| STANDARDS & COMPLIANCE | |
| Product Certifications | CAN/CSA C22.2; CAN/CSA-C22.2 No. 60950-1 (Canada); UL 60950-1 |
| Product Compliance | RoHS; CE (Europe); REACH; FCC Part 15 Class A (USA); Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |