



Circular Connectors IP68
Circular Connectors AC 167 micro
AC 167 RST/2 6-7



plug, 2 pole, voltage rating: 500 V, current rating: 10 A

Order Info

reference number (ref.no.)	72206216
PU	200
EAN	4028012125999

Type

type	plug
number of poles	2 pole
clamping units per pole	1
colour	black
coding	1 (mains)
cross-section rating	1.0 mm ²
connection type	screw
protection against incorrect plugging	yes
latch	yes

Technical Data

voltage rating	500 V
current rating	10 A
impulse voltage rating	4.0 kV
insulating material	PA 6.6
contact material	brass
core cross-section min.	0.25 mm ²
core cross-section max.	1.0 mm ²
protection class	SK II
flammability rating	V-0
max. ambient temperature operation	60 °C
IP code	IP66/IP68/IP69
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	10.0 mm
dismantling length	20.0 mm

assembly contact screw	M2 - max. \cup 0,2 Nm
assembly strain relief	\cup 1.5 Nm
cable diameter min.	5.8 mm
cable diameter max.	6.9 mm
strain relief	yes

Accessories

AC 167 RVKS M16	729042
AC 167 RWZ/2	729044
AC 167 WKZ	729041
DR 10 1x5,5	729051
DR 10 2x2,5	729052
DR 10 3x2,5	729053