HellermannTyton

Specification Sheet

Part Number: 181-23002



Solid wall construction provides excellent coverage to keep wires clean. Durable material protects wires from damage, with long-lasting performance.

Available standard colors complement or contrast in light and dark environments.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.

Solid Wall Wiring Duct, 2" x 3", Non-Adhesive, PVC, White, 120ft/Carton

Article Number	181-23002
Туре	SD2X3
Color	White (WH)
Quantity Per	carton
Product Description	HellermannTyton Solid Wall Wiring Duct efficiently routes and protects wire. Solid wall wiring duct is designed for straight wire runs where breakouts are not required. Solid wall wiring duct is manufactured from high-impact, rigid PVC; comes in standard colors of white, gray and black; and is available in 6-foot lengths.
Short Description	Solid Wall Wiring Duct, 2" x 3", Non-Adhesive, PVC, White, 120ft/Carton

Global Part Name

Length L (Imperial)	6.0	
Length L (Metric)	1.83	
Fixation Method	Non-Adhesive	
Width W (Imperial)	2.0	
Width W (Metric)	50.8	
Height H (Imperial)	3.07	
Height H (Metric)	77.9	
Mounting Hole Centers (Imperial)	4.0	

Material	Polyvinylchloride (PVC)	
Material Shortcut	PVC	
Flammability	Self-extinguishing	
Halogen Free	No	
Operating Temperature	+122°F (+50°C)	

Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Certification/Specification	CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A UL
UL Recognized (US)	Yes
Package Quantity (Imperial)	120.0
Package Quantity (Metric)	36.58
Customs Number	3925900000

© 2023 HellermannTyton. All Rights Reserved.			
Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions