

3-Port USB-C Hub with LAN Port and Power Delivery, USB-C to 3x USB-A, Gbe, 60W PD Charging, USB 3.0, Black

MODEL NUMBER: U460-003-3AGB-C











USB 3.1 hub adds USB-A, Gigabit Ethernet and USB-C charging ports to your laptop, MacBook or other compatible device.

Features

USB-C Hub Connects to Your Device's USB-C or Thunderbolt 3 PortThis USB 3.1 hub expands the potential of your tablet, laptop, Chromebook, MacBook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for connecting to a wired Gigabit Ethernet network, adding a thumb drive and other USB peripherals, and powering and charging a PD Charging-compliant mobile device—all at the same time.

Accesses a Wired Gigabit Ethernet NetworkThe RJ45 port offers access to a Gigabit Ethernet network when no Wi-Fi is available or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

Connects Up to 3 USB-A PeripheralsThree USB-A ports accept USB peripherals, such as a flash drive, mouse, keyboard or printer, and the dedicated fast-charging port provides up to 5V 1.5A (7.5W) for charging smartphones and other mobile devices. All ports support fast USB 3.1 Gen 1 data transfer rates up to 5 Gbps and are backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices. *Note: Host must support USB OTG (On-the-Go)*.

Charges a Connected DeviceThe USB-C Power Delivery (PD) port provides power and charging to the PD Charging-compliant device (such as a MacBook, Chromebook or Android smartphone) the USB-C network adapter is connected to. Connect the device's AC wall charger to the USB-C PD port, which supports power input up to 60W. **Note:** USB-C PD port does not support Quick Charge (QC).

Built-In USB-C Cable Connects in Either DirectionConnect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Ready to Use Right Out of the PackageThe plug-and-play USB 3.1 hub requires no software, drivers or external power. The compact unit fits easily into a pocket, briefcase or laptop bag for connecting on the go. Plug it into your laptop for instant network connection.

Highlights

- Connects you to a wired Ethernet network when Wi-Fi is slow or unavailable
- Supports USB 3.1 Gen 1 speeds up to 5 Gbps to ensure fast data transfers
- Accepts up to 3 USB peripherals, turning your laptop into a mini workstation
- USB-A fast-charging port provides up to 5V 1.5A (7.5W) of power
- Powers and charges PD Charging-compliant devices, such as MacBooks and Chromebooks

Applications

- Access a wired Ethernet network in a location with no or spotty Wi-Fi
- Upload data from your notebook or download data from the Ethernet at true 10/100/1000 Mbps Ethernet speeds
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Transfer files to and from a USB thumb drive or external hard drive
- Write a report using a USB keyboard with your tablet or Android smartphone

System Requirements

Tablet, laptop, Chromebook, MacBook, smartphone or PC with USB-C or Thunderbolt 3 port

Package Includes

- U460-003-3AGB-C 3-Port USB-C Hub. Black
- Owner's manual



Specifications

OVERVIEW UPC Code 03732299184 Product Type Hub Schnology Cat5/5c; Cat6 Host Connector USE C (MALE) VIDEO VIDEO Video Ports (3) USB A (FEMALE) Extended Mode No Mirror Mode No DATA DATA DATA SEA (FEMALE) Data Ports (3) USB A (FEMALE) DATA NETWORK NETWORK NetWORK Novork Ports Mat (FEMALE) Product Length (no) 8 Product Length (mo) 15.24 Product Len				
Product Type Hub Technology Cat5/5e; Cat6 Host Connector USB C (MALE) VIDEO Number of Monitors Supported 0 Video Ports (3) USB A (FEMALE) Extended Mode No MIT Mode DATA Data Ports (3) USB A (FEMALE) Data Ports (3) USB A (FEMALE) NETWORK Network Ports R.945 (FEMALE) Network Ports R.945 (FEMALE) Product Length (in.) 6 Product Length (in.) 6 Product Length (in.) 0.5 Product Length (in.) 0.5 Battery Charging (SV/1,5A Port) Yes Power Power Consumption (Watts) 2.50 USB Power Delivary (PD) Charging Ves	OVERVIEW			
Technology Casifise; Casi6 Host Connector USB C (MALE) VIDEO Number of Monitors Supported 0 Video Ports (3) USB A (FEMALE) Extended Mode No Mirror Mode DATA DATA DATA (3) USB A (FEMALE) Data Ports (3) USB A (FEMALE) Data Ports Details (3) USB A (FEMALE) NETWORK Network Ports R.J45 (FEMALE) Network Ports R.J45 (FEMALE) Product Length (in.) 6 Product Length (in.) 6 Product Length (in.) 0.5 Product Length (in.) 0.5 BATTERY Battery Charging (SV/1.5A Port) Yes Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes USB Power Delivery (PD) Charging Yes	UPC Code	037332209184		
VIDEO ViDEO Video Ports (3) USB A (FEMALE) Extended Mode No Mirror Mode No DATA Data Ports (3) USB A (FEMALE) Data Ports Details (3) USB-A - USB 3.2 Gen 1 (5 Gbps) NETWORK Network Ports RJ45 (FEMALE) Bus Powered Yes Product Length (m.) 6 Product Length (m.) 15.24 Product Length (m.) 15.24 Product Length (m.) 0.5 Product Length (m.) 0.5 Battery Charging (5V/1.5A Port) Yes POWER Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes USB Power Delivery (PD) Charging Yes	Product Type	Hub		
VIDEO Number of Monitors Supported 0 Video Ports (3) USB A (FEMALE) Extended Mode No Mirror Mode DATA Data Ports (3) USB A (FEMALE) Data Ports Details (3) USB-A - USB 3.2 Gen 1 (5 Gbps) NETWORK Network Ports RJ45 (FEMALE) INPUT Bus Powered Yes Product Length (m.) 6 Product Length (m.) 15.24 Product Length (m.) 0.5 Product Length (m.) 0.15 Battery Charging (5V/1.5A Port) Yes POWER Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes USB Power Delivery (PD) Charging Yes	Technology	Cat5/5e; Cat6		
Number of Monitors Supported 0 Video Ports (3) USB A (FEMALE) Extended Mode No Mirror Mode No DATA Data Ports (3) USB A (FEMALE) Data Ports Details (3) USB-A - USB 3.2 Gen 1 (5 Gbps) NETWORK Network Ports RJ45 (FEMALE) INPUT Bus Powered Yes Product Length (in.) 6 Product Length (in.) 6.5 Product Length (in.) 0.5 Product Length (in.) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes Power Power Consumption (Watts) 2.50 USP power Delivery (PD) Charging Yes USP power Delivery (PD) Charging Yes	Host Connector	USB C (MALE)		
Video Ports (3) USB A (FEMALE) Extended Mode No MATA DATA DATA Ports Data Ports Details (3) USB A (FEMALE) Data Ports Details NETWORK NetWork Ports Bus Powered Product Length (in.) 6 Product Length (in.) 0.5 Product Length (in.) 0.15 BATTERY Power Power Power Consumption (Watts) 2.50 USER Nover Delivery (PD) Charging Support Yes	VIDEO			
Extended Mode No Mirror Mode No DATA Data Ports (3) USB A (FEMALE) Data Ports Details (3) USB A - USB 3.2 Gen 1 (5 Gbps) NETWORK Nework Ports RJ45 (FEMALE) INPUT Bus Powered Yes Product Length (in.) 6 Product Length (em.) 15.24 Product Length (ft.) 0.5 Product Length (m.) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes POWER Power Consumption (Watts) 2.50 USBP power Delivery (PD) Charging Support Yes USBP power Delivery (PD) Charging Support Yes	Number of Monitors Supported	0		
Mirror Mode No DATA Data Ports (3) USB A (FEMALE) Data Ports Details (3) USB-A - USB 3.2 Gen 1 (5 Gbps) NETWORK Network Ports RJ45 (FEMALE) INPUT Bus Powered Yes Product Length (in.) 6 Product Length (em.) 15.24 Product Length (it.) 0.5 Product Length (m) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes POWER Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes Yes USBR INTERFACE, ALERTS & CONTROLS	Video Ports	(3) USB A (FEMALE)		
DATA Data Ports (3) USB A (FEMALE) Data Ports Details (3) USB-A - USB 3.2 Gen 1 (5 Gbps) NETWORK Network Ports RJ45 (FEMALE) INPUT Bus Powered Yes Product Length (in.) 6 Product Length (em.) 15.24 Product Length (m.) 0.5 Product Length (m.) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes POWER Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes Yes USER INTERFACE, ALERTS & CONTOLS	Extended Mode	No		
Data Ports (3) USB A (FEMALE) Data Ports Details (3) USB-A - USB 3.2 Gen 1 (5 Gbps) NETWORK	Mirror Mode	No		
Data Ports Details (3) USB-A - USB 3.2 Gen 1 (6 Gbps) NETWORK Network Ports RJ45 (FEMALE) INPUT Bus Powered Yes Product Length (in.) 6 Product Length (cm.) 15.24 Product Length (ft.) 0.5 Product Length (m.) 0.15 BATTERY Batery Charging (5V/1.5A Port) Yes Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging (SV/1.5A Port) Yes USB Power Delivery (PD) Charging (SV/1.5A Port) Yes	DATA			
NETWORK Network Ports R.J45 (FEMALE) INPUT Bus Powered Yes Product Length (in.) 6 Product Length (em.) 15.24 Product Length (it.) 0.5 Product Length (m.) 0.15 Battery Battery Charging (5V/1.5A Port) Yes Power Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes USER INTERFACE, ALERTS & CONTROLS	Data Ports	(3) USB A (FEMALE)		
Network Ports RJ45 (FEMALE) INPUT INPUT Bus Powered Yes Product Length (in.) 6 Product Length (cm.) 15.24 Product Length (ft.) 0.5 Product Length (m.) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes POWER Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Support Yes USER INTERFACE, ALERTS & CONTACTORS	Data Ports Details	(3) USB-A - USB 3.2 Gen 1 (5 Gbps)		
INPUT Bus Powered Yes Product Length (in.) 6 Product Length (rt.) 15.24 Product Length (m.) 0.5 Product Length (m.) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes POWER Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes USER INTERFACE, ALERTS & CONTOLS	NETWORK			
Bus Powered Yes Product Length (in.) 6 Product Length (rm.) 15.24 Product Length (ft.) 0.5 Product Length (m.) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes USER INTERFACE, ALERTS & CONTROLS	Network Ports	RJ45 (FEMALE)		
Product Length (in.) 6 Product Length (cm.) 15.24 Product Length (ft.) 0.5 Product Length (m.) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes Power Consumption (Watts) 2.50 USER INTERFACE, ALERTS & CONTROLS	INPUT			
Product Length (cm.) 15.24 Product Length (ft.) 0.5 Product Length (m.) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes POWER Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes USER INTERFACE, ALERTS & CONTROLS	Bus Powered	Yes		
Product Length (ft.) 0.5 Product Length (m.) 0.15 BATTERY Battery Charging (5V/1.5A Port) Yes POWER Power Consumption (Watts) 2.50 USB Power Delivery (PD) Charging Yes USER INTERFACE, ALERTS & CONTROLS	Product Length (in.)	6		
Product Length (m.) BATTERY Battery Charging (5V/1.5A Port) POWER Power Consumption (Watts) USB Power Delivery (PD) Charging yes Ves USER INTERFACE, ALERTS & CONTROLS	Product Length (cm.)	15.24		
Battery Charging (5V/1.5A Port) POWER Power Consumption (Watts) USB Power Delivery (PD) Charging Support Yes USER INTERFACE, ALERTS & CONTROLS	Product Length (ft.)	0.5		
Battery Charging (5V/1.5A Port) POWER Power Consumption (Watts) USB Power Delivery (PD) Charging Support Yes USER INTERFACE, ALERTS & CONTROLS	Product Length (m.)	0.15		
Power Consumption (Watts) USB Power Delivery (PD) Charging Support USER INTERFACE, ALERTS & CONTROLS	BATTERY			
Power Consumption (Watts) USB Power Delivery (PD) Charging Support Yes USER INTERFACE, ALERTS & CONTROLS	Battery Charging (5V/1.5A Port)	Yes		
USB Power Delivery (PD) Charging Yes USER INTERFACE, ALERTS & CONTROLS	POWER			
USER INTERFACE, ALERTS & CONTROLS	Power Consumption (Watts)	2.50		
	USB Power Delivery (PD) Charging Support	Yes		
LED Indicators Green (Power), Orange (Activity)	USER INTERFACE, ALERTS & CON	USER INTERFACE, ALERTS & CONTROLS		
	LED Indicators	Green (Power), Orange (Activity)		



CHARGING		
Total Charging Watts	60	
Charging Ports	USB-C: 60W (20V 3A) Power Delivery (PD 2.0); USB-A: 5V 1.5A (7.5W)	
Charging Ports / Amps	(2) 0.9A; (1) 1.5A; (1) 3A	
PHYSICAL		
Color	Black	
Material of Construction	Plastic	
Cable Jacket Rating	VW-1	
Shipping Dimensions (hwd / in.)	1.00 x 4.00 x 5.60	
Shipping Weight (lbs.)	0.20	
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000	
Unit Packaging Type	Вох	
Unit Weight (lbs.)	0.09	
Unit Weight (kg)	0.04	
ENVIRONMENTAL		
Operating Temperature Range	32 to 113 F (0 to 45 C)	
Storage Temperature Range	14 to 158 F (-10 to 70 C)	
Relative Humidity	10% to 90% RH, Non-Condensing	
BTUs	8.5 BTU/Hr	
Power Provided to Connected Device(s)	Up to 20V 3A (60W) Input (USB-C), 5V 1.5A (7.5A) Output USB port	
COMMUNICATIONS		
Network Compatibility	1 Gbps (Gigabit)	
IEEE Standards Supported	802.3; 802.3az; 802.3u; 802.3x	
CONNECTIONS		
Number of Ports	5	
Side A - Connector 1	USB C (MALE)	
Side B - Connector 1	(3) USB 3.0 A (FEMALE)	
Side B - Connector 2	RJ45 (FEMALE)	
Side B - Connector 3	USB C (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		



USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Driver Required	No	
Recommended Category Cable	Cat5e/Cat6	
UASP Support	Yes	
Auto MDIX Support	Yes	
Full Duplex Support	Yes	
Suspend Mode Support	Yes	
Remote Wakeup Support	Yes	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.