

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
			APPLICABLE CABLE	CABLE DIAMETER : $\phi 6.3 \pm 0.5$
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK Unless otherwise specified, refer to JIS C 5402.		APPROVED	A0. SUZUKI	09. 04. 16
		CHECKED	MO. SHIMOYAMA	09. 04. 16
		DESIGNED	TS. ITO	09. 04. 14
		DRAWN	TS. ITO	09. 04. 14
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-126657-00	
	SPECIFICATION SHEET	PART NO.	DH-17-CMB (6. 3)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0031-5-00	1/1