NEW 4-OUTLET WALL-MOUNTED ENERGY SAVING POWER GATE SURGE PROTECTOR



Model: ES4SPC

Features

- Energy Saving POWER GATE Technology
- (1) Master outlet with ability to control (2) power saving outlets
- (1) Always on outlet
- LED diagnostics
- Direct plugin converts 2 outlets to 4 outlets
- Joule Rating 2610
- UL1449 4th Edition
- Coax Cable protection
- Phone / DSL protection
- Compact profile
- Fixed outlet mounting
- 5-year warranty

Applications

- Display advertising panels
- Workstation panels
- Video panels
- Home theater
- Home office

General Information

Surge Protection Solutions

The ITW Linx **ES4SPC** is a low profile direct plugin AC surge protection device designed with power saving outlet capabilities. "Master" outlet controls power saving outlets. When the "Master" is on, the power savers are on. When the "Master" is off, the power savers are off. Protects flat panel displays, office work station equipment and home theater devices.

Technical Specifications

Output Frequency Compatibility	50/60 Hz
Output Receptacles	(4) 5-15R
Output (watts)	1800
Circuit Breaker (amps)	15
Input Voltage	120 VAC
Install Type	Direct Plugin
Diagnostic LEDs	Yes

	i.
COAX Protection	Yes
Phone/DSL Protection	Yes
UL 1449 4th Edition suppression rating	L-N 400V L-G 400V N-G 400V
Single Pulse Energy Dissipation	2610 Joules
AC Suppression Response Time	< 1 ns
Unit Dimensions	W= 3.5"; L= 6.0"; D= 1.3"
Unit Weight	0.65 lbs.

