

## Isobar 6-Outlet Under-Monitor Surge Protector, 8 ft. (2.43 m) Cord, 3150 Joules, 2 USB Ports, Diagnostic LEDs, Tel/Fax/Modem

MODEL NUMBER: MT-6PLUS



Premium protection for home/office computer and peripherals against dangerous power surges, spikes and line noise. Low-profile design installs beneath your computer monitor for arm's-length control over connected devices.

### Features

**Network-Grade 3150-Joule Surge Protection for Your Home or Office Electronics** Protects your home/office computer and its peripherals against even the strongest surges and spikes Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Blocks disruptive EMI/RFI line noise up to 80 dB that can cause equipment damage or data loss Exceeds IEEE 587 Category A and B surge suppression specifications RJ11 jacks protect fax, phone and modem signals

**6 Outlets Accept Wide Range of Electronic Devices** 6 NEMA 5-15R AC outlets accept most computers, printers, routers and other peripherals Front-panel master button provides one-touch control over most connected equipment 4 outlets controlled individually via separate front-panel buttons 1 outlet stays on 24/7 for equipment that requires constant power, such as router or modem

**2 USB Charging Ports** Deliver up to 2.1A for charging smartphones, tablets and other mobile devices On/off controlled by front-panel master button

**Premium Safety Features** Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required Diagnostic LEDs confirm power, protection and line fault status at a glance Conforms to current UL 1449 3rd Edition safety standards

**Fits Effortlessly Into Your Setup** 8-ft. (2.43 m) AC power cord with NEMA 5-15P plug reaches nearby outlets Low-profile design fits beneath monitor or laptop for convenient control at arm's length Included mat rests on top of unit to protect surface finish

**Backed by Tripp Lite's Ultimate Lifetime Insurance** \$100,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

### Highlights

- 6 NEMA 5-15R surge-protected rear outlets
- Network-grade 3150-joule surge protection rating
- Low-profile design fits beneath monitor or laptop
- Fax/telephone line/modem surge protection
- 8-ft. (2.43 m) AC power cord with NEMA 5-15P plug

### Package Includes

- MT-6PLUS Isobar® 6-Outlet Under-Monitor Surge Protector
- RJ11 telephone cable, 6-ft. (1.83 m)
- Protective mat
- Owner's manual

## Specifications

| <b>OVERVIEW</b>                              |  |
|--|--|
| UPC Code                                     | 037332010681   |
| Product Type                                 | Surge Protector  |
| Charging Form Factor                         | Strip  |
| Device Compatibility                         | Phone; Tablet; Amazon Kindle   |
| <b>INPUT</b>                                 |  |
| Nominal Input Voltage(s) Supported           | 120V AC  |
| Recommended Electrical Service               | 120V (110-125V)  |
| Input Cord Gauge Type                        | 14 gauge; SJT  |
| Input Cord Gauge (AWG)                       | 14   |
| Voltage Compatibility (VAC)                  | 120  |
| Maximum Surge Amps                           | 84000  |
| Input Plug Type                              | NEMA 5-15P   |
| Input Cord Details                           | SJT  |
| Input Cord Length (ft.)                      | 8  |
| Right-Angle Plug                             | No   |
| Input Cord Length (m)                        | 2.44   |
| Integrated Cord Clip                         | No   |
| <b>OUTPUT</b>                                |  |
| Frequency Compatibility                      | 50 / 60 Hz   |
| Output Receptacles                           | (6) 5-15R  |
| Circuit Breaker (amps)                       | 15   |
| Transformer Accommodation                    | (3) Yes  |
| Right-Angle Outlets                          | No   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Diagnostic LED(s)                            | Yes  |
| Switches                                     | Includes 5 front panel switches - MASTER SWITCH controls all output receptacles (except the one marked "unswitched"), INDIVIDUAL OUTLET switches control 4 individual output receptacles |
| Diagnostic LED Details                       | PROTECTION PRESENT (green), GROUNDED (red), LOW OK (yellow) , MASTER(green), MONITOR, PRINTER, AUX1 AND AUX2(blue)   |
| <b>CHARGING</b>                              |  |
| Number of Charging Ports                     | 2  |
| Total Charging Watts                         | 10.5   |

|                                     |   |
|-------------------------------------|---|
| Charging Method                     | USB   |
| Charging Port Type                  | USB A (FEMALE)  |
| Charging Ports / Amps               | (2) 2.1A  |
| Overcharge Protection               | No  |
| <b>SURGE / NOISE SUPPRESSION</b>    |   |
| AC Suppression Joule Rating         | 3150  |
| AC Suppression Response Time        | NM = 0 ns. CM = <1 ns   |
| Protection Modes                    | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression                        |
| AC Suppression Surge Current Rating | 132,000 amps  |
| AC Suppression Components Used      | Metal oxide varistors, toroidal balanced chokes and VHF capacitors                                  |
| Safe Thermal Fusing                 | Prevents unsafe conditions during extreme extended over-voltages and catastrophic occurrences       |
| UL1449 Let Through Rating           | 330 L-G, 400 L-N, 400 N-G   |
| IEEE587 Cat. A Ringwave Let-Through | Less than 35 volts  |
| EMI / RFI Filtering                 | 40-80 dB  |
| Immunity                            | Conforms to IEE 587 / ANSI C62.41   |
| Automatic Shut-Off                  | Yes   |
| <b>DATALINE SURGE SUPPRESSION</b>   |   |
| Telephone/DSL Protection Details    | 1 line  |
| Cable (Coax) Protection             | No  |
| Network (Ethernet) Protection       | No  |
| Telephone/DSL Protection            | Yes   |
| <b>PHYSICAL</b>                     |   |
| Material of Construction            | Plastic   |
| Power Cord Color                    | Black   |
| Form Factors Supported              | Supports under monitor placement as a power control center for an entire PC system with peripherals |
| Housing Color                       | Black   |
| Mounting Holes or Slots             | No  |
| Receptacle Color                    | Black   |
| Shipping Dimensions (hwd / in.)     | 2.25 x 11.80 x 12.50  |
| Shipping Dimensions (hwd / cm)      | 5.72 x 29.97 x 31.75  |
| Shipping Weight (lbs.)              | 3.60  |
| Shipping Weight (kg)                | 1.63  |

|  |   |
|--|---|
| Unit Dimensions (hwd / in.)                                | 1.700 x 12.500 x 9.530  |
| Unit Dimensions (hwd / cm)                                 | 4.32 X 31.75 X 24.21  |
| Unit Weight (lbs.)   | 3.88  |
| Unit Weight (kg)   | 1.76  |
| <b>FEATURES &amp; SPECIFICATIONS</b>                       |   |
| Rotatable Outlets  | No  |
| Antimicrobial  | No  |
| GaN Technology   | No  |
| <b>STANDARDS &amp; COMPLIANCE</b>                          |   |
| Product Certifications                                     | CAN/CSA-C22.2 No. 21 (Canada); CAN/CSA-C22.2 No. 269.3 (Canada); cUL Listed; UL 1283; UL 1449; UL 497A; UL 1363; UL Listed          |
| Product Compliance   | FCC Part 68; RoHS   |
| <b>WARRANTY &amp; SUPPORT</b>                              |   |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$100,000&nbsp;<a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp; |