

“Stay Connected” with



HEYware Products

a PennEngineering® Company

## Heyco® Polyurethane Adhesive-Back Bumpers



	PART DIMENSIONS				PART NO.		DESCRIPTION	Pieces per Sheet
	A Diameter		B Height		Clear	Black		
	in.	mm.	in.	mm.				
<b>HBA Series - Hemi</b>								
	.25	6,4	.06	1,6	<b>N040</b>	<b>N140</b>	HBA 250-06	578
	.31	7,9	.09	2,3	<b>N027</b>	<b>N127</b>	HBA 312-09	450
<b>NEW!</b>	.34	8,6			<b>NSD027</b>	-	HBA 312-09-SD	
<b>NEW!</b>	.38	9,7	.15	3,8	<b>N007</b>	<b>N107</b>	HBA 335-09	200
	.38	9,7			<b>NSD007</b>	-	HBA 335-09-SD	
<b>NEW!</b>	.38	9,7	.21	5,3	<b>N012</b>	<b>N112</b>	HBA 375-15	288
<b>NEW!</b>	.39	9,9			<b>NSD012</b>	-	HBA 375-15-SD	
<b>NEW!</b>	.39	9,9	.12	3,0	<b>N022</b>	<b>N122</b>	HBA 375-21	300
<b>NEW!</b>	.44	11,2			<b>NSD022</b>	-	HBA 375-21-SD	
<b>NEW!</b>	.44	11,2	.20	5,1	<b>N010</b>	<b>N110</b>	HBA 394-12	288
<b>NEW!</b>	.62	15,7			<b>NSD010</b>	-	HBA 394-12-SD	
	.70	17,8	.38	9,7	<b>N002</b>	<b>N102</b>	HBA 440-20	242
	.75	19,1			<b>NSD002</b>	-	HBA 440-20-SD	
	.70	17,8	.38	9,7	<b>N015</b>	<b>N115</b>	HBA 620-31	128
	.75	19,1			<b>NSD015</b>	-	HBA 620-31-SD	
	.70	17,8	.38	9,7	<b>N008</b>	<b>N108</b>	HBA 700-38	98
	.75	19,1			<b>NSD008</b>	-	HBA 700-38-SD	
	.75	19,1	.08	1,9	<b>N039</b>	<b>N139</b>	HBA 750-08	84
	.75	19,1			<b>NSD039</b>	-	HBA 750-08-SD	
<b>CBA Series - Cylinder</b>								
<b>NEW!</b>	.38	9,7	.13	3,2	<b>N034</b>	<b>N134</b>	CBA 370-13	300
	.38	9,7			<b>NSD034</b>	-	CBA 370-13-SD	
	.38	9,7	.19	4,8	<b>N035</b>	<b>N135</b>	CBA 370-19	200
	.38	9,7			<b>NSD035</b>	-	CBA 370-19-SD	
	.50	12,7	.06	1,5	<b>N005</b>	<b>N105</b>	CBA 500-06	200
<b>NEW!</b>	.50	12,7			<b>NSD005</b>	-	CBA 500-06-SD	
	.50	12,7	.14	3,6	<b>N001</b>	<b>N101</b>	CBA 500-14	200
<b>NEW!</b>	.50	12,7			<b>NSD001</b>	-	CBA 500-14-SD	
	.65	16,5	.40	10,2	<b>N006</b>	<b>N106</b>	CBA 500-25	128
<b>NEW!</b>	.65	16,5			<b>NSD006</b>	-	CBA 500-25-SD	
	.75	19,1	.16	4,1	<b>N011</b>	<b>N111</b>	CBA 650-40	98
<b>NEW!</b>	.75	19,1			<b>NSD011</b>	-	CBA 650-40-SD	
	.78	19,8	.20	5,1	<b>N044</b>	<b>N144</b>	CBA 750-16	84
	.78	19,8			<b>NSD044</b>	-	CBA 750-16-SD	
	.81	20,6	.12	3,0	<b>N041</b>	<b>N141</b>	CBA 780-20	72
<b>NEW!</b>	.81	20,6			<b>NSD041</b>	-	CBA 780-20-SD	
	1.23	31,2	.10	2,5	<b>N024</b>	<b>N124</b>	CBA 810-12	32
<b>NEW!</b>	1.23	31,2			<b>NSD024</b>	-	CBA 810-12-SD	
<b>TCBA Series - Tapered Cylinder</b>								
<b>NEW!</b>	.38	9,7	.18	4,6	<b>NSD067</b>	-	TCBA 375-18-SD	<b>NEW STYLE</b> 288
<b>NEW!</b>	.72	18,2	.56	14,2	<b>N037</b>	<b>N137</b>	TCBA 720-56	1
<b>CDDB Series - Pocket</b>								
<b>NEW!</b>	.50	12,7	.14	3,6	<b>N018</b>	<b>N118</b>	CDDB 500-14	200
	.88	22,4	.40	10,2	<b>NSD018</b>	-	CDDB 500-14-SD	72
	1.81	46,0	.60	15,2	<b>N030</b>	<b>N130</b>	CDDB 1810-60	1
<b>RCDBA Series - Reverse Cylindrical Depression</b>								
<b>NEW!</b>	.50	12,7	.20	5,1	<b>NSD058</b>	-	RCDBA 500-20-SD	<b>NEW STYLE</b> 200
<b>TBA Series - Square or Tapered</b>								
	.40	10,2	.10	2,5	<b>N020</b>	<b>N120</b>	TBA 4040-10	242
	.50	12,7	.12	3,0	<b>N009</b>	<b>N109</b>	TBA 5050-12	200
	.50	12,7			<b>N03R</b>	<b>N13R</b>	TBA 5050-23	
<b>NEW!</b>	.78	19,8	.25	6,4	<b>N029</b>	<b>N129</b>	TBA 7878-25	98
<b>NEW!</b>	.78	19,8			<b>N004</b>	<b>N104</b>	TBA 7878-38	
	.81	20,6	.30	7,6	<b>N019</b>	<b>N119</b>	TBA 8181-30	98
<b>NEW!</b>	.81	20,6			<b>NSD019</b>	-	TBA 8181-30-SD	
	1.00	25,4	.18	4,6	<b>N036</b>	<b>N136</b>	TBA 100100-18	5
<b>NEW!</b>	1.00	25,4			<b>NSD036</b>	-	TBA 100100-18-SD	
<b>RPBA Series - Round Pyramid</b>								
<b>NEW!</b>	.50	12,7	.15	3,8	<b>NSD033</b>	-	RPBA 500-15-SD	<b>NEW STYLE</b> 200

Standard colors clear and black. For white, gray or brown consult Heyco.  
NSD refers to soft durometer Polyurethane (Shora A 45-55) and will not be available in Black.

Material	Polyurethane
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E196663
Flammability Rating	HB
Temperature Range	0°F (-18°C) to 180°F (82°C)

- Quick and easy installation—simply peel off backing and press into place. With no holes to drill, and no screws or rivets needed, adhesive backed bumpers will save you time and money.
- Bumpers can be attached to a wide variety of surfaces; aluminum, ceramic, formica, glass, painted surfaces, polyethylene, polypropylene, vinyl, and steel.
- Adhesive backed bumpers are nonmarking, nonstaining, skid, and scratch resistant.
- Surface must be clean, dry, and free of grease, oil, and other common solvents to obtain maximum adhesion. Clean surfaces with low strength solvents such as Isopropyl Alcohol or Heptane.
- Bumpers have a rubber-based pressure sensitive adhesive with an end use temperature of 0°F (-18°C) to 180°F (82°C).

