

## Specification Sheet

Part Number: 151-01113

HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications. Highly engineered designs feature anti-rattle discs, anti-rotation oval flanges and clamps for mounting on edges.

An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.



Connector Clip, 1.4" Long, PA66HIRHS, Black, 5000/box

Article Number 151-01113

Type EC46

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip, 1.4" Long, PA66HIRHS, Black, 5000/box

|                                |  |
|--------------------------------|--|
| Global Part Name               | EC46-PA66HIRHSUV-BK  |
| Length L (Imperial)            | 1.4  |
| Length L (Metric)              | 35.5   |
| Variant                        | 1.0 - 3.0 mm Edge  |
| Width W (Imperial)             | 0.44   |
| Width W (Metric)               | 11.18  |
| Height H (Imperial)            | 0.56   |
| Height H (Metric)              | 14.15  |
| Panel Thickness Min (Imperial) | 0.04   |
| Panel Thickness Max (Imperial) | 0.12   |
| Panel Thickness Min (Metric)   | 1.0  |
| Panel Thickness Max (Metric)   | 3.0  |
| Material                       | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut              | PA66HIRHSUV  |

|                              |                                   |
|------------------------------|-----------------------------------|
| Flammability                 | UL 94 HB                          |
| UV Resistant (Yes/No)        | Yes                               |
| Operating Temperature        | -40°F to +230°F (-40°C to +110°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 5000                              |
| Package Quantity (Metric)    | 5000                              |
| Customs Number               | 3926909988                        |

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)