




## Han-Fast Lock 4-6mm<sup>2</sup>, Ag



Part number	09 08 000 7923
Specification	Han-Fast Lock 4-6mm <sup>2</sup> , Ag

### Identification

Category	Contacts
Series	Han-Fast <sup>®</sup> Lock
Type of contact	PCB contact
Description of the contact	Without pin

### Version

Pack contents	Single contact
---------------	----------------

### Technical characteristics

Conductor cross-section	4 ... 6 mm <sup>2</sup>
Operating current	≤60 A
Contact resistance	≤2 mΩ
Stripping length	7.5 mm

### Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (locking)	Copper alloy
Surface (locking)	Passivated
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

REACH SVHC substances Not contained

California Proposition 65 substances Yes

## Specifications and approvals

UL / CSA UL 1977 ECBT2.E235076  
CSA-C22.2 No. 182.3 ECBT8.E235076

## Commercial data

Packaging size 100

Net weight 1.22 g

Country of origin Germany

European customs tariff number 85366990

GTIN 5713140014893

eCl@ss 27460201 PCB connector (board connector)