



Status display, Display: LED, Mounting type: Plug in, Colour: Beige

	Βυ	Isine	SS C	lata
--	----	-------	------	------

Article number	<u>1116.2</u>
Article name	SST/SIK/LED(RD)/115V DC/230V AC
GTIN (EAN)	4044211017972
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	1.8 g
Weight per piece (including packaging)	2.56 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Status display
Colour	Beige

Data sheet 1116.2 SST/SIK/LED(RD)/115V DC/230V AC

Technical data		
Connection data		
Connection principle	Plug in	
Materials		
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Plug in	
Voltage illuminated display	115 DC / 230 AC V	
Cross-current via illuminated display	< 5 mA	
Type of display element (defect display)	LED	
Supply voltage (defect display), min.	115	
Supply voltage (defect display), max.	230	
Type of voltage (defect display)	AC/DC	
Colour of lamp	Red	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-01-17	
REACH Candidate Substance Note	No	
RoHS Conform	yes	





Data sheet 1116.2 SST/SIK/LED(RD)/115V DC/230V AC

AD	provals	

Standards and regulations		
EAC approval	TR ZU 004/2011	
EAC approval granted	yes	





Media

EHC

Accessories

Terminal blocks



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

CONTACLIP

Article number	Article name	GTIN (EAN)	Packaging unit
17043.2	SIK 10/Z/ST BG	4044211155810	25 ST



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17042.2	SIK 10/ST BG	4044211155797	25

Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1101.2</u>	SIK 10 BG	4044211016388	50



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1102.2	SIK 10/Z BG	4044211016395	25 ST

##INVERSE##CONTA-CONNECT



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17043.2	SIK 10/Z/ST BG	4044211155810	25 ST



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17042.2	SIK 10/ST BG	4044211155797	25

Data sheet 1116.2 SST/SIK/LED(RD)/115V DC/230V AC

ZCONTACLIP

##INVERSE##CONTA-CONNECT



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1101.2	SIK 10 BG	4044211016388	50



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17044.2	SIK 10/ST/5x20 BG	4044211155827	25 ST



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17044.2	SIK 10/ST/5x20 BG	4044211155827	25 ST