

## Dual-Port USB Car Charger, 63W Max - USB-C PD 3.0 Up to 60W, USB-A QC 3.0 Up to 18W

MODEL NUMBER: U280-C02-63W-1B



2-port car charger quickly and safely charges 2 tablets, smartphones and other USB-C or USB-A devices at the same time.

### Features

**USB Car Charger Safely Charges 2 Mobile Devices in Your Vehicle Simultaneously** This dual-port USB car charger with Power Delivery (PD) 3.0 and Quick Charge (QC) 3.0 technology lets you quickly and safely charge two USB mobile devices at the same time. You and a passenger can connect your smartphones, tablets, notebooks or power banks, to name just a few compatible devices, to ensure satisfactory battery charge when you reach your destination.

**A Combined 63W of Charging Power Feeds Your Power-Hungry Devices** When used together, the USB-C PD 3.0 and USB-A QC 3.0 ports support up to 63W of charging power. The fast-charging USB-C port, when used alone, provides up to 60W (5V 3A, 9V 3A, 12V 3A, 15V 3A or 20V 3A) to keep your larger devices, such as a USB-C laptop, at capacity. Instead of charging at a preset power level, the 18W USB-A port adjusts to the appropriate power level (3.3–6.5V 3A, 6.5–9V 2A or 9–12V 1.5A) to provide as much charge as your QC-compliant device's battery can handle.

**Plugs into the 12V DC Power Outlet in Your Vehicle** The compact charger connects to any standard 12V DC vehicle power outlet, such as the one on your dashboard. Just plug it in, and connect your devices' USB cables for fast, convenient mobile charging. An easy-to-see blue LED indicates the charger is receiving power. A Red LED will indicate the USB-C PD port is in Fast-Charge Mode. The U280-C02-63W-1B is compatible with Apple (including iPhone), Android (including Samsung), Windows and Amazon devices with USB-A, USB-C or Thunderbolt 3 charging ports.

## Specifications

OVERVIEW	
UPC Code	037332254054
Product Type	Car Charger
Charging Form Factor	Direct Plug-In

### Highlights

- 2-port USB charger connects to the 12V DC power outlet in your car, truck or SUV
- Ideal for charging smartphones, tablets, e-readers and notebooks while traveling
- Maximum charging power output of 63W: 45W USB-C and 18W USB-A
- Prevents overheating and overcharging to shield your essential device from damage
- USB-C Power Delivery 3.0 port charges up to 4x faster than conventional USB chargers

### Applications

- Charge up to 2 smartphones, tablets, power banks, e-readers, notebooks or any other USB-A, USB-C or Thunderbolt 3 devices while driving to your destination

### System Requirements

- Vehicle with standard 12V DC power outlet

### Package Includes

- U280-C02-63W-1B Dual-Port USB Car Charger, Black

Device Compatibility	Phone; Tablet; Amazon Kindle; Laptop; Chromebook
Technology	Thunderbolt
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	12V DC
Input Connection Type	Automatic Vehicle Cigarette Lighter
Input Plug Type	Car Auxiliary Power Outlet
Product Length (in.)	2.56
Product Length (cm.)	6.5
Product Length (ft.)	0.21
Product Length (m.)	0.065
<b>OUTPUT</b>	
Output Capacity (Watts)	63
Overload Protection	Yes
<b>POWER</b>	
USB Power Delivery (PD) Charging Support	Yes
USB Power Delivery (PD) Charging Specification	3.0
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
LED Indicators	Blue (Power); Red (Fast-Charge Mode)
<b>CHARGING</b>	
Number of Charging Ports	2
Total Charging Amps	3
Total Charging Watts	63
Charging Method	USB
Charging Method Detail	USB-A: Quick Charge 3.0; USB-C: Power Delivery 3.0
Charging Port Type	USB A (FEMALE); USB C (FEMALE)
Charging Ports Details	USB-A: 3.6-6.5V/3A, 6.5-9V/2A, 9-12V/1.5A (QC 3.0)USB-C: 5V/9V/12V/15V/20V/3A (PD 3.0)
Charging Ports / Amps	(2) 3A
<b>PHYSICAL</b>	
Color	Black
Material of Construction	ABS, PVC
Unit Dimensions (hwd / in.)	1.340 x 2.560 x 1.370

Unit Dimensions (hwd / cm)	3.4 x 6.5
Unit Packaging Type	Polybag
Unit Weight (lbs.)	0.08
Unit Weight (kg)	0.04
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 77°F (0° to 25°C)
Storage Temperature Range	-4° to 140°F (-20° to 60°C)
Operating Humidity Range	30% to 90% RH
Storage Humidity Range	10% to 90% RH
<b>CONNECTIONS</b>	
Number of Ports	2
Side A - Connector 1	Car Cigarette Lighter
Side B - Connector 1	USB A (FEMALE)
Side B - Connector 2	USB C (FEMALE)
<b>INPUT TRANSFORMER</b>	
Input Voltage	12V to 24V
<b>FEATURES &amp; SPECIFICATIONS</b>	
GaN Technology	No
Overcurrent Protection	Yes
Overvoltage Protection	Yes
Quick Charge Compliant	3.0
Driver Required	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	2-year limited warranty



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States



© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.