



May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| APPLICABLE STANDARD   |                                       |                          |  |   |   |
|---|---------------------------------------|--------------------------|--|---|---|
| RATING  | OPERATING TEMPERATURE RANGE           | -25°C TO +85°C           | STORAGE TEMPERATURE RANGE                                      | -25°C TO +60°C  |   |
|   | OPERATING&STORAGE HUMIDTY RANGE       | 85%MAX                   | APPLICABLE CABLE   |  CABLE DIAMETER : φ5.1~7.1 |   |
|   | VOLTAGE                               |                          | CURRENT  |   |   |
| SPECIFICATIONS  |                                       |                          |  |   |   |
| ITEM  | TEST METHOD                           | REQUIREMENTS             | QT   | AT  |   |
| CONSTRUCTION  |                                       |                          |  |   |   |
| GENERAL EXAMINATION   | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING.    | X  | X   |   |
| MARKING   | CONFIRMED VISUALLY.                   |                          | X  | X   |   |
|   |                                       |                          |  |   |   |
|   | COUNT                                 | DESCRIPTION OF REVISIONS | DESIGNED   | CHECKED   | DATE  |
|    | 1                                     | DIS-E-00003216           | KN. ICHIKAWA   | TU. TANIGUCHI   | 20201019  |
| REMARK  |                                       |                          | APPROVED   | KN. ICHIKAWA  | 20100705  |
| THIS PRODUCT SHALL BE MATED WITH DH40-17S OR DH3*B-17S, IT APPLIES TO DH40-17S OR DH3*B-17S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.<br><br>Unless otherwise specified, refer to IEC 60512. |                                       |                          | CHECKED  | KN. ICHIKAWA  | 20100705  |
|   |                                       |                          | DESIGNED   | TU. TANIGUCHI   | 20100705  |
|   |                                       |                          | DRAWN  | TU. TANIGUCHI   | 20100705  |
|   |                                       |                          | Note QT:Qualification Test AT:Assurance Test X:Applicable Test |   |   |
|    | SPECIFICATION SHEET                   |                          | PART NO.   | DH-17-CV2B  |   |
|   | HIROSE ELECTRIC CO., LTD.             |                          | CODE NO.   | CL244-0013-3-00   |  1/1 |