# Product data sheet Characteristics

# GPEFC11

# Auxiliary contact block, Easy TeSys GP2E, 1NO +1NC



Product availability: Stock - Normally stocked in distribution facility

Price\*: 12.50 USD



#### Main

Range	Easy TeSys	
Device short name	GPEFC	
Product or Component Type	Auxiliary contact block	
Mounting Location	Front side	
Pole contact composition	1 NO + 1 NC	
Connections - terminals	Screw clamp terminals 1 0.000.00 in² (12.5 mm²) - solid  Screw clamp terminals 2 0.000.00 in² (12.5 mm²) - solid  Screw clamp terminals 1 0.000.00 in² (0.752.5 mm²) - flexible without cable end  Screw clamp terminals 2 0.000.00 in² (0.752.5 mm²) - flexible without cable end  Screw clamp terminals 1 0.000.00 in² (0.751.5 mm²) - flexible with cable end	
Quantity per Set	Set of 10	

#### Complementary

Complementary	
[Ui] rated insulation voltage	300 V UL 60947-4-1 300 V cUL 250 V IEC 60947-1
[Ue] rated operational voltage	24240 V AC 2460 V DC
[Ith] conventional free air thermal current	2.5 A
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A
Mechanical durability	100000 Cycles
Minimum switching current	5 MA
Minimum switching voltage	17 V
Rated operational power in VA	120 VA 110120 V AC-15 100000 cycles 120 VA 230240 V AC-15 100000 cycles 48 VA 24 V AC-15 100000 cycles 60 VA 48 V AC-15 100000 cycles
Rated operational power in W	15 W 48 V DC-13 100000 cycles 24 W 24 V DC-13 100000 cycles 9 W 60 V DC-13 100000 cycles
Tightening torque	12.39 Lbf.In (1.4 N.m) screw clamp terminals
Height	0.43 ln (11 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelbality or intelbality or intelpacts or application is seed for determining suitability or label products with respect to the relevant specific application or use thereof. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. \*Prices are indicative

Width	1.77 ln (45 mm)	
Depth	1.14 ln (29 mm)	
Net Weight	0.04 Lb(US) (0.02 kg)	

## Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

## Ordering and shipping details

Category	22364-EASY TESYS GP2E1
Discount Schedule	l13
GTIN	3606481063496
Returnability	Yes
Country of origin	CZ

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.50 ln (1.27 cm)
Package 1 Width	1.30 ln (3.3 cm)
Package 1 Length	1.80 ln (4.57 cm)
Package 1 Weight	0.04 Lb(US) (0.02 kg)
Unit Type of Package 2	S02
Number of Units in Package 2	220
Package 2 Height	5.91 ln (15 cm)
Package 2 Width	11.81 ln (30 cm)
Package 2 Length	15.75 ln (40 cm)
Package 2 Weight	10.75 Lb(US) (4.877 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	

Produc	ct Life Status :	Commercialised	

