

Data sheet

2243.0 BS 25 VT



Mounting screw, M 2.5, Colour: Violet

Business data

Article number	<u>2243.0</u>
Article name	BS 25 VT
GTIN (EAN)	4044211050665
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	2.85 g
Weight per piece (including packaging)	2.86 g
Unit of weight	G
Customs number	74153300
Country of origin	DE
Product description	Mounting screw
Colour	Violet

Technical data

Dimensions

Outer diameter	7 mm
----------------	------

Connection data

Screw head	Slotted
------------	---------

Screw threading	M 2,5
-----------------	-------

Tightening torque, min.	0.4 Nm
-------------------------	--------

Tightening torque, max.	0.8 Nm
-------------------------	--------

Materials

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

Surface screw	Nickel
---------------	--------

Further technical data

Mounting type	Screwable
---------------	-----------

Insulation available	✓
----------------------	---

Environmental Product Compliance

REACH Conform	No
---------------	----

REACH Reference date	2023-01-17
----------------------	------------

REACH Candidate Substance Note	No
--------------------------------	----

REACH CAS 1 Substance	LEAD
-----------------------	------

REACH CAS 1 Percent minimal	0.1 %
-----------------------------	-------

REACH CAS 1 Percent maximum	4 %
-----------------------------	-----

REACH CAS 1 Number	7439-92-1
--------------------	-----------

RoHS Conform	yes
--------------	-----

RoHS Exception rule	6c
---------------------	----


Media



Accessories


##INVERSE##CONTA-CONNECT

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige




Article number	Article name	GTIN (EAN)	Packaging unit
17523.2	SPTK 6/LT/HB BG	4044211209223	50 ST

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige



Article number	Article name	GTIN (EAN)	Packaging unit
17524.2	SPTK 6/LT/STBI/YE BG	4044211209919	50 ST

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige



Article number	Article name	GTIN (EAN)	Packaging unit
17520.2	SPTK 6/DU BG	4044211209650	50 ST

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige



Article number	Article name	GTIN (EAN)	Packaging unit
17521.2	SPTK 6/LT BG	4044211209162	50 ST

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige



Article number	Article name	GTIN (EAN)	Packaging unit
17522.2	SPTK 6/QT BG	4044211209216	50 ST

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige



Article number	Article name	GTIN (EAN)	Packaging unit
17525.2	SPTK 6/LT/STBI/BU BG	4044211209926	50 ST

##INVERSE##CONTA-CONNECT

Data sheet

2243.0 BS 25 VT



Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5,
Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>17521.2</u>	SPTK 6/LT BG	4044211209162	50 ST