

Specification Sheet

Part Number: 596-00247

Made with UV-stable inks and materials for durability and weather resistance
Polyester is resistant to chemicals and solvents and will remain legible in dirty environments
High abrasion and scuff resistance for high-performance labeling
Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections

CAUTION: SOLAR CIRCUIT

Solar Label, Reflective, CAUTION SOLAR CIRCUIT, 6.5" x 1.0", VL, Red, 50/pkg

Article Number 596-00247

Type CSCIRLBL

Color Red (RD)

Quantity Per roll

Product Description HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, Reflective, CAUTION SOLAR CIRCUIT, 6.5" x 1.0", VL, Red, 50/pkg
Global Part Name	CSCIRLBL-V-RD
Width W (Imperial)	6.5
Width W (Metric)	165.1
Thickness T (Metric)	64.0
Height H (Imperial)	1.0
Height H (Metric)	25.40
Material	Vinyl (V)
Material Shortcut	V
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL 969 IFC 2012 NEC2011
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1