





APPLICABLE STANDARD																												
RATING	OPERATING TEMPERATURE RANGE	-35°C TO 85°C (NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C TO 60°C																								
	VOLTAGE	30V AC	APPLICABLE CONNECTOR	DF37*-*DP-0. 4V (**)																								
	CURRENT	0. 3A																										
SPECIFICATIONS																												
ITEM	TEST METHOD	REQUIREMENTS	QT	AT																								
CONSTRUCTION																												
GENERAL EXAMINATION	CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X																								
MARKING	CONFIRMED VISUALLY.		X	X																								
ELECTRIC CHARACTERISTICS																												
CONTACT RESISTANCE	20mV AC OR LESS 1kHz,1m A .	100mΩ MAX.	X	-																								
INSULATION RESISTANCE	100V DC.	50MΩ MIN.	X	-																								
VOLTAGE PROOF	100V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	-																								
MECHANICAL CHARACTERISTICS																												
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	 <table border="1"> <thead> <tr> <th></th> <th>ISNERTION FORCE</th> <th>SITHDRAWAL FORCE</th> </tr> <tr> <th>PIN COUNT</th> <th>(N MAX)</th> <th>(N MIN)</th> </tr> </thead> <tbody> <tr> <td>20</td> <td>24.3</td> <td>4.4</td> </tr> <tr> <td>24</td> <td>27.8</td> <td>5.1</td> </tr> <tr> <td>30</td> <td>33.1</td> <td>6.2</td> </tr> <tr> <td>34</td> <td>40.8</td> <td>6.9</td> </tr> <tr> <td>40</td> <td>41.9</td> <td>8.0</td> </tr> <tr> <td>60</td> <td>59.5</td> <td>11.7</td> </tr> </tbody> </table>		ISNERTION FORCE	SITHDRAWAL FORCE	PIN COUNT	(N MAX)	(N MIN)	20	24.3	4.4	24	27.8	5.1	30	33.1	6.2	34	40.8	6.9	40	41.9	8.0	60	59.5	11.7	X	-
				ISNERTION FORCE	SITHDRAWAL FORCE																							
			PIN COUNT	(N MAX)	(N MIN)																							
			20	24.3	4.4																							
			24	27.8	5.1																							
			30	33.1	6.2																							
34	40.8	6.9																										
40	41.9	8.0																										
60	59.5	11.7																										
MECHANICAL OPERATION	10TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
VIBRATION	FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min, SINGLE AMPLITUDE 0.75 mm, 10CYCLES, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
ENVIRONMENTAL CHARACTERISTICS																												
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → 85 °C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN 2 ~3 MIN)	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 25MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
SULPHUR DIOXIDE	EXPOSED IN 25 PPM FOR 96h, 25°C, 75%. (REFER TO JIS C 60068)	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
SALT MIST	EXPOSED IN 5% SALT MIST FOR 48h.	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE																								
 1	DIS-H-00003087	YT. TAKAGI	TS. MIYAZAKI	17. 09. 28																								
REMARKS		APPROVED	KH. IKEDA	10. 02. 08																								
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT		CHECKED	TS. MIYAZAKI	10. 02. 08																								
Unless otherwise specified, refer to JIS C 5402 and IEC 60512		DESIGNED	RT. SHIMIZU	10. 02. 08																								
		DRAWN	RT. SHIMIZU	10. 02. 05																								
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-329590-01																									
	SPECIFICATION SHEET	PART NO.	DF37SB-*DS-0. 4V (51)																									
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL684	 1/1																								