

28185.7 PVC-TAA 20X72 K WH

Device and installation marker, Length: 72 mm, Width: 20 mm, Colour: White

RAL: 9010

Business data

Article number	28185.7
Article name	PVC-TAA 20X72 K WH
GTIN (EAN)	4044211213527
Packaging unit	50
Quantity unit	PC
Number of markers per card	5 ST
Weight per piece (not including packaging)	3.65 g
Weight per piece (including packaging)	3.65 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Prio-Article	28185.7
Product description	Device and installation marker

28185.7 PVC-TAA 20X72 K WH

Technical data

Dimensions

Length	72 mm
Width	20 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Self-adhesive
Software code	851

Environmental Product Compliance

REACH Conform	yes
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

28185.7 PVC-TAA 20X72 K WH

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST