

## Han Q 4/2female insert with Quick Lock



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 12 006 2763  |
| Specification      | Han Q 4/2female insert with Quick Lock  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09120062763">https://b2b.harting.com/09120062763</a> |

### Identification

|                |                    |
|----------------|--------------------|
| Category       | Inserts            |
| Series         | Han <sup>®</sup> Q |
| Identification | 4/2                |

### Version

|                           |  |
|---------------------------|--|
| Termination method        | Axial screw termination                          |
| Gender                    | Female   |
| Size                      | Han-Compact <sup>®</sup>                         |
| Number of contacts        | 6  |
| Number of signal contacts | 2  |
| Number of power contacts  | 4  |
| PE contact                | Yes  |
| Details                   | With Han-Quick Lock <sup>®</sup> signal contacts |

### Technical characteristics

|                                       |   |
|---------------------------------------|---|
| Conductor cross-section               | 4 ... 10 mm <sup>2</sup><br>0.25 ... 1.5 mm <sup>2</sup> Signal |
| Rated current (signal)                | 10 A  |
| Rated voltage (signal)                | 250 V   |
| Rated impulse voltage (signal)        | 4 kV  |
| Pollution degree (signal)             | 3   |
| Rated current (power)                 | 40 A  |
| Rated voltage conductor-earth (Power) | 400 V   |



Pushing Performance  
Since 1945

## Technical characteristics

|   |                            |
|---|----------------------------|
| Rated voltage conductor-conductor (Power) | 690 V                      |
| Rated impulse voltage (power)             | 6 kV                       |
| Pollution degree (power)                  | 3                          |
| Insulation resistance                     | $>10^{10} \Omega$          |
| Contact resistance                        | $\leq 0.3 \text{ m}\Omega$ |
| Contact resistance, signal area           | $< 3 \text{ m}\Omega$      |
| Tightening torque                         | 1.8 Nm                     |
| Limiting temperature                      | -40 ... +125 °C            |
| Mating cycles                             | $\geq 500$                 |

## Material properties

|   |  |
|---|--|
| Material (insert)                         | Polycarbonate (PC)                                     |
| Colour (insert)                           | RAL 7032 (pebble grey)                                 |
| Material (contacts)                       | Copper alloy   |
| Surface (contacts)                        | Silver plated  |
| Material flammability class acc. to UL 94 | V-0  |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                                | compliant with exemption                               |
| China RoHS                                | 50   |
| REACH Annex XVII substances               | Not contained  |
| REACH ANNEX XIV substances                | Not contained  |
| REACH SVHC substances                     | Yes  |
| REACH SVHC substances                     | Lead   |
| ECHA SCIP number                          | 5dbb3851-b94e-4e88-97a1-571845975242                   |
| California Proposition 65 substances      | Yes  |
| California Proposition 65 substances      | Lead   |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08)                                   |
| Requirement set with Hazard Levels        | R22 (HL 1-3)<br>R23 (HL 1-3)                           |

## Specifications and approvals

|                |                          |
|----------------|--------------------------|
| Specifications | IEC 60664-1<br>IEC 61984 |
|----------------|--------------------------|



**Pushing Performance**  
Since 1945

## Specifications and approvals

|           |  |
|-----------|--|
| Approvals | DNV GL   |
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |

## Commercial data

|                                |   |
|--------------------------------|---|
| Packaging size                 | 10  |
| Net weight                     | 37.56 g   |
| Country of origin              | Romania   |
| European customs tariff number | 85366990  |
| GTIN                           | 5713140017399                                     |
| eCl@ss                         | 27440205 Contact insert for industrial connectors |