## CENTER 385 REFRIGERANT LEAK DETECTOR Features: • Microprocessor Control with advanced digital signal processing. Multi color visual display. High-Med-Low sensitivity selector.

- Low battery indication.
- Semiconductor gas sensor.
- Detection of R-134a, R-410A, R-407C, R22... Freon gas.
- Carrying case included.
- 15.5" (40 CM) flexible stainless probe.
- Reference Leak source included.
- Ambient concentration reset.
- Long-life, DC brushless fan
- Variable intensity audible and visual alarms







## FEATURES

Air Sucking System for faster response and higher sensitivity.

Refrigerant Leakage Detector is the perfect tool for maintaining the air-condition or a cooling system with compressor and Refrigerant.

This unit used newly developed semi-conductor sensor which is extremely sensitive to variety of general used Refrigerant.

Microprocessor Control with advanced digital signal processing.

## SPECIFICATIONS

- Heated Semiconductor Gas Sensor.
- 3 Levels Of Sensitivity.
- 7 LED Tri-colored Visual Leak Level Indicator.
- Variable Intensity Audible Alarm.
- Ambient Concentration Reset.
- 15.5"(40CM) Flexible Stainless Probe.
- Detection of R-134a, R-404A, R-410A, R-407C, R-22, R-502, R-600A...Refrigerants Gas.
- Sensitivity As Small 3gr/year.
- Accordance With SAE J1627, CE Design.
- Low Battery Indication.
- Reference Leak Source Included.
- Hard Carrying case Included.
- Warm-up Time: 45 Seconds.
- Operating Temperature: 0 to 40°C(32 to 104°F)
- Dimensions: 22.2 x 6.6 x 5.1 cm
- Weight: 418g(with batteries)
- Power Source: 2 x Size C Alkaline Batteries.
- AC Adapter: @3.3V 0.5A







\* The specifications and other information in this catalogue are subject to change without prior notice.



4/F., NO.415, Jung-Jeng Rd., 23868 Shu-Lin, Taipei, Taiwan TEL: 886-2-26763926 E-Mail: center@centertek.com FAX: 886-2-26763925 http://www.centertek.com

Distributed b	y
---------------	---