

Han ID Module Socket Profinet



| Part number | 09 80 615 0200 |
|--------------------|-------------------------------------|
| Specification | Han ID Module Socket Profinet |
| HARTING eCatalogue | https://b2b.harting.com/09806150200 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Modules |
|---------------------------|---|
| Series | Han-Modular [®] |
| Identification | Han-Smart [®] |
| Type of module | ID Profinet |
| Size of the module | Single module |
| Description of the module | Power supply Data interface with HARTING ix Industrial [®] (Typ A) |
| Features | Module for identifying industrial components Profinet I/O communication protocol conformance class B SNMP enabled (V1, V2C) |

Version

| Gender | Female |
|--------------------|---|
| Number of contacts | 7 |
| Diagnostic display | Connection (Link) Power connection |
| Details | GSD software file and operating instructions can be downloaded from the eCatalogue. |
| Termination data | |
| Nominal voltage | 24 V DC ±10 % |
| Power consumption | <2 W |

Technical characteristics

| Operating temperature -40 +70 °C |
|----------------------------------|
|----------------------------------|

Page 1 / 2 | Creation date 2023-03-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Technical characteristics

| Storage temperature | -40 +70 °C |
|--|----------------------|
| Mating cycles | ≥500 |
| Degree of protection acc. to IEC 60529 | IP20 |
| Real-time class | RT acc. to IEC 61158 |

Material properties

| Material (insert) | Polycarbonate (PC) Liquid crystal polymer (LCP) |
|---|--|
| Colour (insert) | RAL 7032 (pebble grey) White |
| Material flammability class acc. to UL 94 | V-0 |

Specifications and approvals

| Specifications | IEC 60721-3-3 |
|----------------|--|
| | EN 61000-4-2 Electrostatic discharge (ESD) |
| | EN 61000-4-3 Electromagnetic field |
| | EN 61000-4-4 Rapid transients (burst) |
| | EN 61000-4-5 Surge voltages |
| | EN 61000-4-6 conducted disturbances |
| | IEC 61158 |
| CE | Yes |
| PROFINET | Yes |
| | |

Commercial data

| Packaging size | 1 |
|--------------------------------|--|
| Net weight | 29.44 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140185074 |
| eCl@ss | 27440218 Module for industrial connectors (data) |

Page 2 / 2 | Creation date 2023-03-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany