



Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 13.1 mm, Colour: Red

Business data	
Article number	27124.9
Article name	PQI 1,5/4 RD
GTIN (EAN)	4044211225186
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	1.32 g
Weight per piece (including packaging)	1.44 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	27124.9
Product description	Insulated cross-connector



Technical data

With13.1 mmHeight14.5 mmPitch size3.5 mmRatings	Dimensions		
Height14.5 mmPitch size3.5 mmRatings500 VMax. voltage500 VRated current17.5 ACurrent load, max.17,5 ARated cross-section1.5 mm²Contamination degree3Connection data100 mm²No. of poles4Materials100 mm²Insulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical data√Mounting typePlug inInsulation available√Number of bridged terminals4Environmental Product ComplianceyesREACH ConformyesREACH Condidate Substance NoteNo	Length	3.2 mm	
Pitch size 3.5 mm Ratings 500 V Max. voltage 500 V Rated current 17.5 A Current load, max. 17.5 A Rated cross-section 1.5 mm² Contamination degree 3 Connection data 1000000000000000000000000000000000000	Width	13.1 mm	
Ratings Max. voltage 500 V Rated current 17.5 A Current load, max. 17.5 A Rated cross-section 1.5 mm² Contamination degree 3 Connection data	Height	14.5 mm	
Max. voltage500 VRated current17.5 ACurrent load, max.17,5 ARated cross-section1.5 mm²Contamination degree3Connection data4No. of poles4MaterialsInsulation housingInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical data✓Mounting typePlug inInsulation available✓Touch protection is available✓Kumber of bridged terminals4Environmental Product ComplianceNoREACH ConformyesREACH ConformyesREACH Candidate Substance NoteNo	Pitch size	3.5 mm	
Rated current17.5 ACurrent load, max.17,5 ARated cross-section1.5 mm²Contamination degree3Connection dataNo. of poles4MaterialsInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation availableInsulation availableInsulation availableReach ConformyesREACH ConformyesREACH Candidate Substance NoteNo	Ratings		
Current load, max.17,5 ARated cross-section1.5 mm²Contamination degree3Connection dataNo. of poles4MaterialsInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation availableVouch protection is availableVNumber of bridged terminals4Environmental Product ComplianceyesREACH ConformyesREACH ConformNo	Max. voltage	500 V	
Rated cross-section1.5 mm²Contamination degree3Connection dataNo. of poles4MaterialsInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals4Environmental Product ComplianceyesREACH ConformyesREACH Candidate Substance NoteNo	Rated current	17.5 A	
Contamination degree3Connection dataNo. of poles4MaterialsInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals4Environmental Product ComplianceREACH ConformyesREACH Candidate Substance NoteNo	Current load, max.	17,5 A	
Connection data No. of poles 4 Materials Insulation housing Polyamide 6.6 Flammability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data Mounting type Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 4 Environmental Product Compliance REACH Conform REACH Candidate Substance Note No	Rated cross-section	1.5 mm ²	
No. of poles4MaterialsInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals4Environmental Product ComplianceyesREACH ConformyesREACH Candidate Substance NoteNo	Contamination degree	3	
MaterialsInsulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals4Environmental Product ComplianceyesREACH ConformyesREACH Candidate Substance NoteNo	Connection data		
Insulation housingPolyamide 6.6Flammability class UL 94V-0Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals4Environmental Product ComplianceREACH ConformyesREACH Candidate Substance NoteNo	No. of poles	4	
Flammability class UL 94 V-0 Working temperature, min. -40 °C Working temperature, max. 120 °C Further technical data Mounting type Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 4 Environmental Product Compliance yes REACH Conform yes REACH Candidate Substance Note No	Materials		
Working temperature, min40 °CWorking temperature, max.120 °CFurther technical dataPlug inMounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals4Environmental Product ComplianceyesREACH ConformyesREACH Candidate Substance NoteNo	Insulation housing	Polyamide 6.6	
Working temperature, max. 120 °C Further technical data Mounting type Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 4 Environmental Product Compliance yes REACH Conform yes REACH Candidate Substance Note No	Flammability class UL 94	V-0	
Further technical data Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 4 Environmental Product Compliance yes REACH Conform yes REACH Candidate Substance Note No	Working temperature, min.	-40 °C	
Mounting typePlug inInsulation available✓Touch protection is available✓Number of bridged terminals4Environmental Product ComplianceREACH ConformyesREACH Candidate Substance NoteNo	Working temperature, max.	120 °C	
Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 4 Environmental Product Compliance ✓ REACH Conform yes REACH Candidate Substance Note No	Further technical data		
Touch protection is available ✓ Number of bridged terminals 4 Environmental Product Compliance ✓ REACH Conform yes REACH Candidate Substance Note No	Mounting type	Plug in	
Number of bridged terminals 4 Environmental Product Compliance REACH Conform yes REACH Candidate Substance Note No	Insulation available	✓	
Environmental Product Compliance REACH Conform yes REACH Candidate Substance Note No	Touch protection is available	\checkmark	
REACH Conform yes REACH Candidate Substance Note No	Number of bridged terminals	4	
REACH Candidate Substance Note No	Environmental Product Compliance		
	REACH Conform	yes	
RoHS Conform yes	REACH Candidate Substance Note	No	
	RoHS Conform	yes	

Media



ZCONTACLIP

Accessories

##INVERSE##CONTA-CONNECT

	Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm ² , Width: 3.5 mm, Colour: Green-yellow				
1.	Article number	Article name	GTIN (EAN)	Packaging unit	
	27001.2	PSL 1,5/2A GNYE	4044211223687	50 ST	
		h terminal, Push-in connection action: 1.5 mm², Width: 3.5 mm	, Mounting type: Mounting rail T a, Colour: Green-yellow	S 35/7.5,	
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27003.2	PSL 1,5/3A GNYE	4044211223724	50 ST	
000	Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm ² , Width: 3.5 mm, Colour: Green-yellow				
1.0	Article number	Article name	GTIN (EAN)	Packaging unit	
	27005.2	PSL 1,5/4A GNYE	4044211223762	50 ST	