



**FIBER TOOLS**

# 1.25mm Adapter

2.5mm (male) to 1.25mm (female) Hybrid Adapter

TESTING | TROUBLESHOOTING | ACCURACY

## Product Features:

- Converts 2.5mm PC/UPC Visual Fault Locator ports to 1.25mm PC/UPC
- For use with LC and MU connectors
- Suitable for use with Optical Power Meters and other Stabilized Light Sources with 2.5mm PC/UPC ports
- Compatible with singlemode and multimode ferrules
- Low insertion loss
- Precision alignment with Zirconia sleeve

## Specifications

Insertion Loss	<0.2dB
Operating Wavelength	1200nm - 1700nm
Fiber Type	Singlemode (9/125um) or Multimode (50/125 um, 62.5/125um)
Ferrule Type	PC type (standard)
Operating Temp.	-40 to +75 °C
Storage Temp.	-40 to +85 °C
Humidity	95%RH
Dimension	0.23" Diameter x 0.9" Long (6mm x 22.9 mm)
Weight	0.18oz (5g)
Sleeve Type	Zirconia Sleeve

## Ordering Information

CAT. NO.	DESCRIPTION
1.25MM ADAPTER	1.25mm Adapter for LC and MU connectors



1390 Aspen Way Vista, CA • 92081

TFT-1.25MMAD

Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 927 050

©2019 Tempo Communications Inc. • An ISO 9001 Company

EMEA Address: Tempo Europe Limited • Brecon House, William Brown Close, Cwmbran • NP44 3AB, UK



Follow us @TempoComms



**TEMPO**  
COMMUNICATIONS

*Renewed Vision. Innovation Forward.*

TempoCom.com | tel 800.642.2155