

Product: <u>9764</u> ☑



CATV Video, RG11, 14 AWG BCCS, Tri Shield, Polyethylene Jacket

Product Description

CATV, Series 11, 14 AWG solid .064" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond Plus®; aluminum braid shield (75% coverage), polyethylene jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor AWG Stranding Material Nominal Diameter No. of Coax 14 Solid BCCS - Bare Copper Covered Steel 0.064 in 1 Conductor Count: 1 Insulation

Outer Shield

| Type | Layer | Material | Material Trade Name | Coverage [%] |
|--|-------|-------------------------------|---------------------|--------------|
| Tape | 1 | Tri-Laminate (Alum+Poly+Alum) | Duobond® II | 100% |
| Braid | 2 | Aluminum | | 75% |
| Tape | 3 | Bi-Laminate (Alum+Poly) | | 100% |
| Table Notes: Tape has shorting fold and is b | | ld and is bonded | | |

Outer Jacket


| Material | Nominal Diameter |
|-------------------|------------------|
| PE - Polyethylene | 0.4 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR | Outer Conductor DCR |
|-----------------------|--------------------------|---------------------|
| 11 Ohm/1000ft | 3.8 Ohm/1000ft | 3.8 Ohm/1000ft |

Capacitance



Inductance

Nominal Inductance 0.097 µH/ft

Impedance

Nominal Characteristic Impedance
75 Ohm

Return Loss (RL)

| Frequency [MHz] | Min. Structural Return Loss (SRL) |
|-----------------|-----------------------------------|
| 5-1000 MHz | 20 dB |

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.2 ns/ft | 83% |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) |
|-----------------|-----------------------------------|
| 5 MHz | 0.38 dB/100ft |
| 55 MHz | 0.96 dB/100ft |
| 211 MHz | 1.9 dB/100ft |
| 270 MHz | 2.13 dB/100ft |
| 300 MHz | 2.25 dB/100ft |
| 350 MHz | 2.42 dB/100ft |
| 400 MHz | 2.6 dB/100ft |
| 450 MHz | 2.75 dB/100ft |
| 550 MHz | 3.04 dB/100ft |
| 750 MHz | 3.65 dB/100ft |
| 870 MHz | 4.06 dB/100ft |
| 1000 MHz | 4.35 dB/100ft |

Voltage

Non-UL Voltage Rating 300 V RMS

Temperature Range

| Non-UL Temp Rating: | 80°C |
|------------------------------|----------------|
| Operating Temperature Range: | -55°C To +80°C |

Mechanical Characteristics

| Bulk Cable Weight: | 52 lbs/1000ft |
|------------------------------|---------------|
| Max. Pull Tension: | 276 lbs |
| Min. Bend Radius/Minor Axis: | 4 in |

Standards

| RG Type: | 11 |
|--------------|----|
| Series Type: | 11 |

Applicable Environmental and Other Programs

| Environmental Space: | Outdoor - Water Exposure |
|--|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (RoHS 2): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU (RoHS 2 amendment): | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | No |
| MII Order #39 (China RoHS): | Yes |

Suitability

| Suitability - Burial: | Yes |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |

Plenum/Non-Plenum

| Plenum (Y/N): | No |
|---------------|----|
|---------------|----|

Related Part Numbers

Variants

| Item # | Color | Put-Up Type | Length | UPC |
|--------------|--------|-------------|----------|--------------|
| 9764 0101000 | Black | Reel | 1,000 ft | 612825258452 |
| 9764 0031000 | Orange | Reel | 1,000 ft | 612825258278 |

History

| Update and Revision: | Revision Number: 0.380 Revision Date: 11-09-2022 |
|----------------------|--|

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.