




USSK28-20MM-3/4"-SS

Ruland USSK28-20MM-3/4"-SS, 20mm x 3/4" Single Universal Joint, Friction Bearing, Stainless Steel, Set Screw With Keyway, 1.745" (44.3mm) OD, 5.000" (127.0mm) Length





Description

Ruland USSK28-20MM-3/4"-SS is a single cardan friction bearing universal joint with 20mm x 0.7500" bores, 6mm x 3/16" keyways, 1.745" (44.3mm) OD, 5.000" (127.0mm) length, and 5/16-18 set screws. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. USSK28-20MM-3/4"-SS is made from high grade stainless steel for increased corrosion resistance. It can be combined with boot UBOOT28/44-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

Bore (B1) 20 mm Small Bore (B2) 0.7500 in Keyway (K1) 6 mm Keyway (K2) 3/16 in B1 Max Shaft Penetration 1.610 in (40.9 mm) B2 Max Shaft Penetration 1.610 in (40.9 mm) Joint Outer Diameter (OD) 1.745 in (44.3 mm) Bore Tolerance +0.0010 in / -0.0000 in / -0.0000 in / -0.0000 in / -0.0000 mm) Length (L) 5.000 in (127.0 mm) Yoke Length (LY) 2.500 in (63.5 mm) Hub Depth (LH) 1.610 in (40.9 mm) Broached Set Screw 5/16-18 Screw Finish Bright Peak Torque 10,500 in-lb (1,186.3 in / 10,500 in-lb (1,186.3 in / 10,500 in-lb (237.3 Nm) Max Operating Angle 45° Material Specification Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel Pins and Blocks: 416 Stainless Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 120 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452934180 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular at the Comment of the comment of the comment of	
B1 Max Shaft Penetration 1.610 in (40.9 mm) B2 Max Shaft Penetration 1.610 in (40.9 mm) Joint Outer Diameter (OD) 1.745 in (44.3 mm) Bore Tolerance +0.0010 in / -0.0000 in / -0.0000 mm) Length (L) 5.000 in (127.0 mm) Yoke Length (LY) 2.500 in (63.5 mm) Hub Depth (LH) 1.610 in (40.9 mm) Broached Set Screw 5/16-18 Screw Finish Bright Peak Torque 10,500 in-lb (1,186.3 ld.) Rated Torque 2,100 in-lb (237.3 Nm) Max Operating Angle 45° Material Specification Yokes: 303 Stainless Steel Manufacturer Belden Universal Pins and Blocks: 416 Stainless Steel Manufacturer Belden Universal Matching Boot Cover USA Recommended Lubricant LUBRIPLATE No. 120 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452934180 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular and particular	
Joint Outer Diameter (OD) 1.745 in (44.3 mm) 8	
A	
Hub Depth (LH)1.610 in (40.9 mm)Broached Set Screw5/16-18Screw FinishBrightPeak Torque10,500 in-lb (1,186.3 ld.)Rated Torque2,100 in-lb (237.3 Nm)Max Operating Angle45°Material SpecificationYokes: 303 Stainless Steel Pins and Blocks: 416 Stainless SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 120Matching Boot CoverUBOOT28/44-NI-KITUPC63452934180Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular and the control of the	า (+0.025 mm
Screw FinishBrightPeak Torque10,500 in-lb (1,186.3 lb)Rated Torque2,100 in-lb (237.3 Nm)Max Operating Angle45°Material SpecificationYokes: 303 Stainless Steel Pins and Blocks: 416 Stainless SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 120Matching Boot CoverUBOOT28/44-NI-KITUPC63452934180Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular and pa	
Rated Torque2,100 in-lb (237.3 Nm)Max Operating Angle45°Material SpecificationYokes: 303 Stainless Steel Pins and Blocks: 416 Stainless SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 120Matching Boot CoverUBOOT28/44-NI-KITUPC63452934180Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular and par	
Material Specification Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 120 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452934180 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular and particular an	Nm)
Pins and Blocks: 416 Stainless Steel Country of Origin USA Recommended Lubricant LUBRIPLATE No. 120 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452934180 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular and the suitability for a particular and th	
Matching Boot CoverUBOOT28/44-NI-KITUPC63452934180Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular and an approximation of the control of the contr	
Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular and a particula	00-2
Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular a	
Pron 65	application.
Prop 65 WARNING This product can expose you to the chemical Nickel (metallic), known to the State to cause cancer. For more information go to www.P65Warnings.ca.gov .	te of California