ATGBICS CPAC-TR-1T-SSM160-SFP+ Checkpoint Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

Brand : ATGBICS

Product code: CPAC-TR-1T-SSM160-SFP+-C

Product name : CPAC-TR-1T-SSM160-SFP+ Checkpoint Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

CPAC-TR-1T-SSM160-SFP+ Checkpoint Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m)

ATGBICS CPAC-TR-1T-SSM160-SFP+ Checkpoint Compatible Transceiver SFP 10/100/1000Base-T (RJ45, Copper, 100m):

ATGBICS CPAC-TR-1T-SSM160-SFP+ SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Checkpoint 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product meets the specification of Checkpoint CPAC-TR-1T-SSM160-SFP+= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type *	Copper 1250 Mbit/s	Certification	CE, FCC, RoHS
Interface type *SFPSingle-mode fiber (SMF) supportedXMulti-mode fiber (MMF) supportedXSFP transceiver standardTX		Power	
	×	Input voltage Maximum voltage Power consumption (typical)	3.3 V 4 V 1.3 W
Maximum transfer distance Ethernet LAN Ethernet interface type	100 m ✓ Gigabit Ethernet 10BASE-T, 100BASE-TX, 1000BASE- TX ✓	Operational conditions Maximum operating temperature Operating temperature (T-T)	70 °C 0 - 70 °C
Copper ethernet cabling technology Auto MDI/MDI-X		Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 - 85 °C 5 - 85% 5 - 85%
Digital Diagnostics Monitoring (DDM)	×	Weight & dimensions	
Features Product colour	Silver Metal ✓ ✓ ✓ United Kingdom	Width Depth Height	13.4 mm 56.6 mm 8.5 mm
Housing material Plug and Play		Weight	24 g
Hot-Plug support		Packaging data	
Hot-swap Easy to install		Number of products included Package type	l pc(s) Box
, ,		Technical details	
	Checkpoint	Sustainability compliance	1



5056468700254

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.