

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		USB3.0 SPECIFICATION AND MICRO-USB CABLE AND CONNECTORS SPECIFICATION.				
RATING	OPERATING TEMPERATURE RANGE	-30°C TO +85°C	STORAGE TEMPERATURE RANGE	-30°C TO +60°C		
	VOLTAGE	-	OPERATING HUMIDITY RANGE	- % TO - %		
	CURRENT	-	APPLICABLE CABLE	OUTER DIAMETER OF CABLE : φ 3.3		
SPECIFICATIONS						
ITEM		TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION						
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING		CONFIRMED VISUALLY.			X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
	1	DIS-E-003550	TS. SAKAI ZAWA	KN. ICHIKAWA	10. 12. 20	
REMARK HIROSE will not guarantee the performance on these specifications In case this product will be mated with the others which is not HIROSE's. Unless otherwise specified, refer to USB3.0 or EIA 364				APPROVED	A0. SUZUKI	09. 06. 16
				CHECKED	KN. ICHIKAWA	09. 06. 16
				DESIGNED	TS. SAKAI ZAWA	09. 06. 15
				DRAWN	TS. SAKAI ZAWA	09. 06. 15
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-127030-00		
	SPECIFICATION SHEET		PART NO.	ZX360-B-SLDA		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL242-0502-7-00		1/1