BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape





ATS Part#: ATS-52190B-C1-R0

Description: 19.00 x 19.00 x 7.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal

Tape

Heat Sink Type: maxiFLOW
Heat Sink Attachment: Thermal Tape

Equivalent Part Number: ATS-52190B-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	16.5 °C/W	13.4 °C/W	11.6 °C/W	10.3 °C/W	9.4 °C/W	8.7 °C/W	8.2 °C/W
	Ducted Flow	12.9	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
	19.00 mm	19.00 mm	7.50 mm	31.54 mm	T412	BLUE-ANODIZED
B	 Dimension ATS-5219 (Saint-Go) Thermal papplication ATS reserperforman ATS certification 	bain C675). berformance data are n. ves the right to update. ies that this heat sin	emponent size. The provided for reference or change its provided for reference to the control of the control o	oly with an equivalent nce only. Actual performation ducts without notice	t thermal formance	interface material may vary by
*Image above is for illustration purpose only.						

