

5-Outlet Surge Protector Tower, 3x USB Ports (3.1A Shared), 6 ft. Cord, 5-15P Plug, 1200 Joules, White

MODEL NUMBER: TLP66USB











Slim surge protection tower with USB charging safeguards your electronics against dangerous surges, spikes and line noise.

Features

Slim 5-Outlet Surge Protection Tower Safeguards Your Sensitive Electronics

Ideal for your home or office workstation, this Protect It!® five-outlet tower features a surge suppression rating of 1200 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP66USB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

5 NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your laptop, external hard drive, desk lamp or other home/office devices into the NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. The outlets are split between two sides of the tower to give everyone equal access to them. They are also spread apart to allow easy connection of bulky transformers without blocking adjacent outlets.

3 USB Ports Share 3.1 Amps of Charging Power

USB-A ports are available for charging your smartphone, tablet and other USB mobile devices. They share 3.1A for charging multiple devices at the same time.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety Features to Maintain Your Equipment's Well-Being

An on/off switch allows you easy one-touch control over all connected equipment. Red and green LEDs confirm at a glance that your plugged-in devices are grounded and protected.

Slim Tower Design Gives You Plenty of Options for Installation and Use

The TLP66USB fits easily into your home or office workspace, conference table or classroom, providing

Highlights

- Ideal for conference tables, home offices and other areas with multiple mobile devices
- 5 NEMA 5-15R outlets spaced widely apart to accommodate bulky transformers
- 1200 joules protect your valuable electronics against dangerous surges and spikes
- 3 USB ports share 3.1A for fast charging of phones, tablets and other mobile devices
- Right-angle NEMA 5-15P plug with braided 6 ft. cord allows connection in tight spaces

Applications

- Ensure critical devices, such as laptops and tablets, stay fully powered and charged during important conferences and meetings
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge a smartphone and tablet without taking up available AC outlets

Package Includes

- TLP66USB 5-Outlet Surge Protector Tower, White
- Owner's manual



power and USB charging at your fingertips. Its slim design also makes the surge protector tower ideal for travel, fitting into your backpack, laptop bag or suitcase for use in hotels, dorms and cruise ships. The braided six-foot power cord and space-saving right-angle NEMA 5-15P plug allows connection in tight spaces, such as behind furniture.

Specifications

OVERVIEW		
UPC Code	037332260321	
Product Type	Surge Protector	
Charging Form Factor	Tower	
Device Compatibility	Amazon Kindle; Laptop; Phone; Tablet	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Input Cord Gauge (AWG)	14	
Maximum Surge Amps	1200	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT-B	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	
Input Cord Length (m)	1.83	
Integrated Cord Clip	No	
ОИТРИТ		
Frequency Compatibility	60 Hz	
Output Receptacles	(5) 5-15R	
Circuit Breaker (amps)	15	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
CHARGING		
Number of Charging Ports	4	
Total Charging Watts	15.5	
Charging Method	USB	
Charging Port Type	USB A (FEMALE)	



Charging Ports / Amps	(3) 3.1A	
Overcharge Protection	No	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1200	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	
UL1449 Let Through Rating	700,700,700	
EMI / RFI Filtering	Yes	
Immunity	Conforms to IEE 587/ANSI C62.41	
Automatic Shut-Off	No	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Material of Construction	Plastic	
Power Cord Color	Gray and White Braided Cord	
Mounting Holes or Slots	Yes	
Receptacle Color	Black	
Unit Dimensions (hwd / in.)	2.000 x 7.080 x 7.080	
Unit Dimensions (hwd / cm)	5.08 x 18 x 18	
Unit Weight (lbs.)	1.8	
Unit Weight (kg)	0.82	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	No	
GaN Technology	No	
STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); NOM (Mexico); UL 1449; UL 497A; UL 1363	
Product Compliance	FCC Part 68; RoHS	
WARRANTY & SUPPORT		



Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$7,500 Ultimate Lifetime Insurance



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.