




USSK32-30MM-22MM-F

Ruland USSK32-30MM-22MM-F, 30mm x 22mm Single Universal Joint, Friction Bearing, Steel, Set Screw With Keyway, 50.7mm OD, 139.7mm Length





Description

Ruland USSK32-30MM-22MM-F is a single cardan friction bearing universal joint with 30mm x 22mm bores, 8mm x 6mm keyways, 50.7mm OD, 139.7mm length, and 3/8-16 set screws. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. USSK32-30MM-22MM-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT32/51-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

					_	•					
1	u	rc	•	11	101	· Cr	$\Delta \alpha$	`I †I	cat	\mathbf{I}	ne
-		·	,,	ı	ı			,,,,	Lai	ıv	HO

Bore (B1)	30 mm	Small Bore (B2)	22 mm			
Keyway (K1)	8 mm	Keyway (K2)	6 mm			
B1 Max Shaft Penetration	43.2 mm	B2 Max Shaft Penetration	43.2 mm			
Joint Outer Diameter (OD)	50.7 mm	Bore Tolerance	+0.025 mm / -0.000 mm			
Length (L)	139.7 mm	Yoke Length (LY)	69.9 mm			
Hub Depth (LH)	43.2 mm	Broached Set Screw	3/8-16			
Screw Finish	Black Oxide	Peak Torque	2429.2 Nm			
Rated Torque	485.8 Nm	Max Operating Angle	45°			
Material Specification	Alloy Steel	Manufacturer	Belden Universal			
Country of Origin	USA	Recommended Lubricant	LUBRIPLATE No. 1200-2			
Matching Boot Cover	UBOOT32/51-NI-KIT	UPC	63452934293			
Tariff Code	8483.60.4000	UNSPC	25173810			
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.					
Prop 65	•	an expose you to the chemical Ethylen d birth defects or other reproductive ha				