

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	 CABLE DIAMETER : φ 8.5~10.1	
	CURRENT		VOLTAGE		
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
	2	DIS-E-00003216	KN. ICHIKAWA	TU. TANIGUCHI	20201019
REMARK			APPROVED	AO. SUZUKI	20090428
THIS PRODUCT SHALL BE MATED WITH DH3*B-51S, IT APPLIES TO DH3*B-51S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to IEC 60512. 			CHECKED	KN. ICHIKAWA	20090428
			DESIGNED	MO. SHIMOYAMA	20090428
			DRAWN	MO. SHIMOYAMA	20090428
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.
	SPECIFICATION SHEET		PART NO.	DH-51-CT1B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0044-7-00	 1/1