

# M23 ComLock-S Hood 11-17 mm



Part number	09 15 100 0483
Specification	M23 ComLock-S Hood 11-17 mm
HARTING eCatalogue	https://b2b.harting.com/09151000483

Image is for illustration purposes only. Please refer to product description.

## Version

Size	M23
Version	Top entry
Locking type	ComLock-S rapid locking
Details	Compatible to Speedtec (TE)

## Technical characteristics

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP67 locked condition IP69 / IPX9K acc. to ISO 20653 locked condition
Clamping range	11 17 mm

# Material properties

Material (hood/housing)	Copper-zinc alloy
Surface (hood/housing)	Nickel plated
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel



# Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076

## Commercial data

Packaging size	5
Net weight	87.9 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140184060
eCl@ss	27440224 Shell for circular connectors