


PC BOARD LAYOUT
RECOMMENDED PC BOARD THICKNESS 1.57 [.062]

- ① HOUSING MATERIAL: GLASS-FILLED POLYMER.
- ② POST MATERIAL: COPPER ALLOY.
- ③ POST FINISH: DIN 41612 CLASS 2 IN CONTACT AREA. TIN PLATE ON POSTS.
- ④ RECOMMENDED HOLE SIZE FOR MANUAL APPLICATION OF CONNECTOR ONTO PC BOARD.
- ⑤ PART NUMBER, DATE CODE MARKED THIS APPROXIMATE AREA.
- ⑥ MARKING ON THIS SIDE.
- ⑦ PACKAGED BY TUBE



REFERENCE FAMILY DRAWING 650473 FOR ALL TYPE C HEADER OFFERINGS

1-5148020-5
5148020-5
PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN J. POLIGNONE DSMAYOS	TE Connectivity
DIMENSIONS: mm [INCHES]		CHK A. SHARPE DSMAYOS	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD A. SHARPE DSMAYOS	NAME
0 PLC ± -		PRODUCT SPEC	ASSEMBLY, PIN, EUROCARD, TYPE 1/2C, 48 POSITION, 2.64 [.104] SOLDER POST WITH BOARD-LOCKS
1 PLC ± -		APPLICATION SPEC	
2 PLC ± -		SIZE	A1
3 PLC ± 0.13 [.005]		WEIGHT	00779 C=5148020
4 PLC ± -		CUSTOMER DRAWING	SCALE 5:1 SHEET 1 OF 1 REV B
ANGLES ± -			