

## ATGBICS QSFP-4SFP10G-CU5M Cisco Compatible Direct Attach Copper Breakout Cable 40G QSFP+ to 4x10G SFP+ (5m, Passive)

**Brand :** ATGBICS

**Product code:** QSFP-4SFP10G-CU5M-C

**Product name :** QSFP-4SFP10G-CU5M Cisco Compatible Direct Attach Copper Breakout Cable 40G QSFP+ to 4x10G SFP+ (5m, Passive)



QSFP-4SFP10G-CU5M Cisco Compatible Direct Attach Copper Breakout Cable 40G QSFP+ to 4x10G SFP+ (5m, Passive)

[ATGBICS QSFP-4SFP10G-CU5M Cisco Compatible Direct Attach Copper Breakout Cable 40G QSFP+ to 4x10G SFP+ \(5m, Passive\):](#)

ATGBICS QSFP-4SFP10G-CU5M compatible 40GBase QSFP+ to 4x10G SFP+ direct attach breakout cable operates over passive copper with a cable length of 5m. It is suitable for very short distances and provides a cost-efficient way to connect hardware within close proximity racks. This breakout cable connects to 1 x 40G QSFP+ port of a switch on one end and to 4 x 10G SFP+ ports of a switch on the other end. Our product meets the specification of Cisco QSFP-4SFP10G-CU5M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 40G InfiniBand 8x DDR, 4x QDR, 10G/40Gigabit Ethernet, Fibre Channel. Connector A is QSFP+ MSA SFF-8436 Compliant and connector B is SFP+ MSA SFF-8431 Compliant.



| Features                |                          | Features                          |                |
|-------------------------|--------------------------|-----------------------------------|----------------|
| Product colour *        | Black                    | Country of origin                 | United Kingdom |
| Cable length *          | 5 m                      | <b>Operational conditions</b>     |                |
| Connector 1 *           | QSFP+                    | Operating temperature (T-T)       | 0 - 70 °C      |
| Connector 2 *           | 4 x SFP+                 | Storage temperature (T-T)         | -40 - 80 °C    |
| Connector 1 gender *    | Male                     | Operating relative humidity (H-H) | 10 - 90%       |
| Connector 2 gender *    | Male                     | Storage relative humidity (H-H)   | 10 - 85%       |
| Jacket material         | Polyvinyl chloride (PVC) | <b>Packaging data</b>             |                |
| Conductor material      | Copper                   | Quantity per pack                 | 1 pc(s)        |
| Ethernet interface type | 40 Gigabit Ethernet      | <b>Technical details</b>          |                |
| Networking standards    | IEEE 802.3ba             | Sustainability compliance         | ✓              |
| AWG wire size           | 24                       | Sustainability certificates       | RoHS           |
| Data transfer rate      | 40000 Mbit/s             | Doesn't contain                   | Lead           |
| Plug and Play           | ✓                        |                                   |                |
| Certification           | CE, FCC, RoHS            |                                   |                |



5056468724502

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-MAY-2023. Prints or copies of Information are only valid on the printed Publication date