


Specification Sheet

Part Number: 133-03178



Inverted retaining legs and narrow opening prevent inadvertent disengagement

Controlled flex and angled entry promote easy installation

Robust arrowhead design provides low insertion effort yet delivers exceptional retention strength in a 65 mm hole in panels from 12 to 16 mm

Tube and Pipe Clip with 6.5mm Arrowhead, 4.7-5.1mm Diameter, PA66HIRHS, Black, 4000/ctn

Article Number 133-03178

Type PC5AH6.5

Color Black (BK)

Quantity Per carton

Product Description This clip features a modular design that can be used individually or lined together to secure multiple pipes or hoses.

Short Description Tube and Pipe Clip with 6.5mm Arrowhead, 4.7-5.1mm Diameter, PA66HIRHS, Black, 4000/ctn

Global Part Name PC5AH6.5-PA66HIRHSUV-BK

Length L (Imperial)	0.67
Length L (Metric)	17.0
Fixation Method	Arrowhead
Width W (Metric)	10.0
Height H (Imperial)	0.86
Height H (Metric)	21.5
Panel Thickness Min (Imperial)	0.05
Panel Thickness Max (Imperial)	0.06
Panel Thickness Min (Metric)	1.2
Panel Thickness Max (Metric)	1.6
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm 6.35 mm (hexagonal)
Disc Diameter (Metric)	17.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV

Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)