

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO 60 °C	STORAGE TEMPERATURE RANGE	1 -25 °C TO 60 °C	
	VOLTAGE		CURRENT		
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
2	DIS-E-00002227	TS. ITO	TU. TANIGUCHI	20190418	
REMARK			APPROVED	HO. MIWA	20050105
1 PACKING MATERIAL IS NOT INCLUDED.			CHECKED	TH. KAMEYA	20050105
Unless otherwise specified, refer to JIS C 5402.			DESIGNED	SS. SATOH	20050105
			DRAWN	SS. SATOH	20050105
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-121484-01		
HRS	SPECIFICATION SHEET	PART NO.	TM21P-88P (**)		
	HIROSE ELECTRIC CO., LTD.	CODE NO.			1/1