



Device and installation marker, Length: 30 mm, Width: 40 mm, Colour: Yellow

RAL: 1026

Business data

Article number	28155.8
Article name	PVC-PTSA 40X30 K YE
GTIN (EAN)	4044211213077
Packaging unit	150
Quantity unit	PC
Number of markers per card	6 ST
Weight per piece (not including packaging)	2.15 g
Weight per piece (including packaging)	2.15 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Prio-Article	28155.6
Product description	Device and installation marker

Technical data

Dimensions

Length	30 mm
Width	40 mm
Hole diameter	22.5 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Unter Bedienelement
Software code	1000

Environmental Product Compliance

REACH Conform	yes
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

28155.8 PVC-PTSA 40X30 K YE

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST
