

## 6788AV Composite - Audio and Video Composite Cable

For more Information  
please call

1-800-Belden1



**Picture  
Not Available**

### General Description:

Video Cable, Plenum-CMP, 6-25 AWG solid tinned copper, foam FEP insulation, Duobond®+95% tinned copper interlocked serve, Flamarrest® jacket, 2 pairs - 22 AWG stranded tinned copper, Flamarrest® insul., Beldfoil® shield, drain wire, Flamarrest® jacket, overall Flamarrest® jacket

### Usage (Overall)

**Suitable Applications:**

Projection Video, Projectors, Classroom, Room-to-Room AV, RGB, VGA, SVGA, XGA, SXGA, USGA, HDTVm LCD, Plasma, Component Video, Video Mult., Composite Audio Video, Hybrid Component, Animation, Special Effects, RGB62TS, RGB6C/22-2P-PLN, High Resolution, HR + STP

### Coax

#### Physical Characteristics

##### Conductor

**AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
6	25	Solid	TC - Tinned Copper	0.457

##### Insulation

**Insulation Material:**

Insulation Material	Dia. (mm)
FPFA - Foam Perfluoroalkoxy	1.880

##### Inner Shield

**Inner Shield Material:**

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	% Coverage (%)
1	Duobond®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Interlocked Serve	TC - Tinned Copper	95

##### Inner Jacket

**Inner Jacket Material:**

Inner Jacket Trade Name	Inner Jacket Material	Nom. Dia. (mm)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	2.896

**Inner Jacket Color Code Chart:**

Number	Color
1	Red
2	Green
3	Blue
4	Yellow
5	Black
6	White

#### Mechanical Characteristics

**Min. Bend Radius (Install):** 27.940 mm

#### Electrical Characteristics

**Nom. Characteristic Impedance:**

Impedance (Ohm)
75

**Nom. Inductance:**

METRIC MEASUREMENT VERSION

## 6788AV Composite - Audio and Video Composite Cable

**Inductance (µH/m)**

0.285

**Nom. Capacitance Conductor to Shield:**

**Capacitance (pF/m)**

55.777

**Nominal Velocity of Propagation:**

**VP (%)**

80.000

**Nominal Delay:**

**Delay (ns/m)**

4.068

**Nom. Conductor DC Resistance:**

**DCR @ 20°C (Ohm/km)**

111.554

**Nom. Inner Shield DC Resistance:**

**DCR @ 20°C (Ohm/km)**

17.717

**Minimum Return Loss:**

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5.000	850.000	20.000

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100m)
1.000	1.706
5.000	3.839
50.000	12.140
100.000	16.077
200.000	21.983
400.000	31.170
750.000	43.965
900.000	49.215
1000.000	51.840
3000.000	102.367

**Max. Operating Voltage - UL:**

300 V RMS

### Twisted Pair

#### Physical Characteristics

##### Conductor

**AWG:**

# Pairs	AWG	Stranding	Conductor Material
2	22	7x30	TC - Tinned Copper

##### Insulation

**Insulation Material:**

Insulation Trade Name	Insulation Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

**Twisted Pair Color Code Chart:**

Number	Color
1	Black and Red
2	Black and Red

##### Inner Shield

**Inner Shield Material:**

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

**Inner Shield Drain Wire AWG:**

## 6788AV Composite - Audio and Video Composite Cable

AWG	Stranding	Conductor Material
24	Stranded	TC - Tinned Copper

### Inner Jacket

#### Inner Jacket Material:

Inner Jacket Trade Name	Inner Jacket Material	Nom. Dia. (mm)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	3.404

#### Inner Jacket Color Code Chart:

Number	Color
1	Brown
2	Orange

### Mechanical Characteristics

**Min. Bend Radius (Install):** 38.100 mm

### Electrical Characteristics

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
150.926

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
52.824

#### Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/km)
37.732

#### Max. Operating Voltage - UL:

Voltage
300 V RMS

#### Max. Recommended Current:

Current
2.8 Amps per conductor @ 25°C

## Physical Characteristics (Overall)

### Conductor

### Overall Cable

#### Overall Cabling Color Code Chart:

Number	Color
1	Red
2	Green
3	Blue
4	Yellow
5	Black
6	White
7	Brown
8	Orange

**Overall Nominal Diameter:** 10.820 mm

## Mechanical Characteristics (Overall)

**Operating Temperature Range:** 0°C To +75°C

**Separation Temperature Range:** 0°C To +75°C

**Bulk Cable Weight:** 122.032 Kg/Km

**Max. Recommended Pulling Tension:** 822.917 N

**Min. Bend Radius/Minor Axis:** 114.300 mm

## 6788AV Composite - Audio and Video Composite Cable

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	02/13/2007
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Applicable Patents:

Country
<a href="http://www.belden.com/p">www.belden.com/p</a>

#### Flame Test

UL Flame Test:	NFPA 262 Plenum Flame Test (UL910)(FT6)
CSA Flame Test:	FT6

#### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	5788AV

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
6788AV 0001000	1,000 FT	99.000 LB	NONE	C	6XRG59 MINI#25+2P22 FS CMP BP
6788AV 000250	250 FT	26.750 LB	NONE	C	6XRG59 MINI#25+2P22 FS CMP BP
6788AV 009250	250 FT	26.750 LB	WHITE	C	6XRG59 MINI#25+2P22 FS CMP BP

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 02-28-2014

© 2019 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).