

Photovoltaic connector - PV-C1F-C-HSG - 1050771

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Photovoltaic connector, Range of articles: Sunclix, Photovoltaic connector, housing material: PPE, color: black, number of positions: 1, min. conductor cross section: 2.5 mm², max. conductor cross section: 6 mm², rated voltage: 1500 V DC, rated current: 40 A, Connection method: Crimp, Type of contact: Socket, min. cable diameter: 5 mm, max. cable diameter: 8 mm

Your advantages

- ✓ Crimp connection technology for automated assembly processes
- ✓ High yield, thanks to silver-plated contacts
- ✓ International approvals in accordance with IEC and UL enable worldwide use
- ✓ Unique SUNCLIX pin connector pattern



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 0 5 5 6 2 6 6 6 9 6 3 2
GTIN	4055626669632
Custom tariff number	85366990
Country of origin	India

Technical data

Item properties

Range of articles	Sunclix
Brief article description	Photovoltaic connector
Product feature	DC connector, 1-pos., socket (+)
Color	black
Connection method	Crimp

Photovoltaic connector - PV-C1F-C-HSG - 1050771

Technical data

Item properties

Type of contact	Socket
Number of positions	1

Product dimensions

Width	20 mm
Height	20 mm
Length	72.8 mm

Rated current	40 A (in accordance with IEC 62852:2014/AMD1:2020)
	34 A (in accordance with IEC 62852:2014/AMD1:2020)
	27 A (in accordance with IEC 62852:2014/AMD1:2020)
	50 A (in accordance with UL 6703)
	35 A (in accordance with UL 6703)
Rated voltage	30 A (in accordance with UL 6703)
	1500 V DCII 2 (in accordance with IEC 62852:2014/AMD1:2020)
	1500 V DC (in accordance with UL 6703)
Protection class	II

Connection data

Min. wire cross section	2.5 mm ²
Max. wire cross section	6 mm ²
Min. wire cross section	14 AWG
Max. wire cross section	10 AWG
Cable diameter	5 mm ... 8 mm
Stripping length of the individual wire	9 mm -1 mm
Torque	max. 3.1 Nm ±0.1 Nm (Cable gland, depending on cable type and outside cable diameter)

Environmental data

Ambient temperature (operation)	-40 °C ... 85 °C (dependent on the derating curve)
Ambient temperature (assembly)	-5 °C ... 50 °C
Limiting temperatures_GRP	105.00 °C

Mechanical tests

Insertion force	45 N ±10 N
-----------------	------------

Service life tests

Degree of protection	IP66 / IP68 (2 m / 24 h) (plugged in)
Insertion/withdrawal cycles	100

Contact material	Cu alloy silver-plated
------------------	------------------------

Photovoltaic connector - PV-C1F-C-HSG - 1050771

Technical data

RTI	105 °C Housing
Contact surface material	Ag
Contact material	Cu
Material	Housing

Detail specification

Detail specification	IEC 62852
----------------------	-----------

Classifications

eCl@ss

eCl@ss 10.0.1	27440107
eCl@ss 11.0	27440107
eCl@ss 9.0	27440107

ETIM

ETIM 7.0	EC002635
----------	----------

Approvals


Approvals

Approvals

UL Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E477377-20211118
Nominal voltage UN	1500 V		
Nominal current IN	50 A		
mm ² /AWG/kcmil	14-10		

Photovoltaic connector - PV-C1F-C-HSG - 1050771

Accessories

Accessories

Crimping tool

Crimping pliers - CRIMPFOX-P SR 6 - 1212755



Crimping pliers, for SUNCLIX solar crimp connectors 2.5 ... 6 mm², unlockable pressure lock, precise parallel crimping, lateral entry, B crimp, incl. positioning tool

Panel feed-through

Device connector, front mounting - PV-C3F-C-6-R3000 - 1050767



Panel feed-through, Range of articles: Sunclix, Device connector, front mounting, color: black, number of positions: 1, min. conductor cross section: 6 mm², max. conductor cross section: 6 mm², Connection method: Crimp, Type of contact: Socket

Device connector, front mounting - PV-C3F-C-2,5-4-R3000 - 1050769



Panel feed-through, Range of articles: Sunclix, Device connector, front mounting, color: black, number of positions: 1, min. conductor cross section: 2.5 mm², max. conductor cross section: 4 mm², rated current: 27 A, Connection method: Crimp, Type of contact: Socket

Photovoltaic connector

Protective cap - PV-C PROTECTION CAP - 1785430



Photovoltaic connector, Range of articles: Sunclix, Protective cap, color: black, self-sealing, without interlock, set consisting of: 1 protective cap for connector side and 1 protective cap for coupling side

Photovoltaic connector - PV-C1F-C-HSG - 1050771

Accessories

Contact removal tool - PV-A-C-DC-TOOL - 1069522

Photovoltaic connector, Range of articles: Sunclix, Contact removal tool

